

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
John Staver

3. ADDRESS OF OPERATOR % Pohlmann & Associates
200 Petroleum Plaza, Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FNL & 1980 FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

I-89-Ind-57

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo tribal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Table Mesa

9. WELL NO.

3418

10. FIELD OR WILDCAT NAME

Table Mesa Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T27N, R17W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and Abandoned as follows by John Cunningham:

- #1. From 7113-6713 (400' inside 5½" casing)
- #2. From 6200-5900 (300' inside 5½" casing)
- #3. From 5017-4917 (100' across bottom of 8 5/8" csg. inside 1" csg.)
- #4. From 4260-4160 (100' inside 5½" casing)
- #5. Cut & pulled 5½" csg from 3360. Placed 50' cement plug inside & above casing stub (3410-3310).
- #6. From 2850-2650 (200' inside 8 5/8" casing.
- #7. Cut & pulled 8 5/8" csg @ 1310'. Spotted plug from 1400-1200 across Dakota.
- #8. Surface plug from 75' to surface.
Heavy mud placed between all plugs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. Belongue TITLE Agent DATE Sept 17, 1979

(This space for Federal or State office use)

TITLE _____

DATE _____

APPROVED BY _____ IF ANY:

SEP 18 1979

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

N Moore

