

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SP**
Lease No. **080382-A**
Unit **Frontier**

X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 30, 1960

Well No. **3-C** is located **1980** ft. from **N** line and **990** ft. from **W** line of sec. **5**
SW/4 NW/4 Section 5 **27N** **11W** **NMPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated Gallup **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6092** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

June 25, 1960 Total Depth 6005'.

Ran 145 joints, 3-1/2", 15.50#, J-55 Casing (5994') set at 6004' with 100 sacks regular cement, 100 sacks Pozmix, 2% gel, 25# Gilsomite/sack. Cemented through two-stage collar at 2105' with 100 sacks regular cement. Held 1000#/30 Minutes. Calc. top of lower cement at 4300'. Top of cement by temperature survey at 1600'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Products Company**

Address **Post Office Box 1560**

Farmington, New Mexico

ORIGINAL SIGNED BY: VAN E. DYKES
By

Title **Petroleum Engineer**

