

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Beta Development Company		8. FARM OR LEASE NAME Holloway Federal
3. ADDRESS OF OPERATOR 238 Petroleum Plaza, Farmington, NM 87401		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FNL & 1650' FEL		10. FIELD AND POOL, OR WILDCAT Basin Dakota
14. PERMIT NO.		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 6, T-27N, R-11W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6042' G.R.		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANE

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17 DES. KILL, PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-26-84

Move in P & A Rig.

Pull 2-3/8" tubing, lay down 2 jt's with holes, reran tubing open ended to 6400', spot 25 sacks class "B" cement in 5 1/2" casing 6210-6400', hole loaded while pumping displacement, had 9.4# drilling mud coming back. Pick tubing up and spot 25 sacks class "B" cement in 5 1/2" casing 5214-5404' Pick tubing up and spot 25 sacks class "B" cement in 5 1/2" casing 2544-2734' Pick tubing up and spot 25 sacks class "B" cement in 5 1/2" casing 1614-1804' Shot 5 1/2" csing off @ 1377' lay down 44 jts + 1-17' cut off tubing open ended to 50' inside casing stub (1377) to 1427'. Pump 35 sacks class "B" cement 1327-1427'. Pick tubing up and spot 60 sacks plug @ 50' below base of Ojo-Alamo @ 750' 700-800. Pick tubing up and spot 60 sacks plug 50' below base of Surface pipe 261-361'.

1-30-84

Cut 10-3/4" surface pipe off 4' below ground level, spot 20 sacks in top of surface. (Irrigation area no dry hole marker required).

RECEIVED

MAR 01 1984

OIL CON. DIV.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DIST. 3

DATE

February 23, 1984

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side