

		X	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. SF-079116
Unit _____
Edgar Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MADE IN NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
OCT 20 1960
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

October 17, 1960

Well No. #2 is located 1650 ft. from {N} line and 1650 ft. from {E} line of sec. 1
SW/4 NE/4 Sec. 1 27N 12W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undes. (Dakota) San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6050 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 9/29/60

Set 10 jts. 10 3/4" 32.75# surface casing @ 319' w/250 sx HA-5 cement, good returns on cement. WOC Tested w/750# held OK.
10/15/60

Set 5 1/2" 15.50# CFI (203 jts 6553') set at 6532' w/225 sx 4% gel. & 75 sx latex cement. Plug down 12:30 AM - cemented second stage thru DV tool w/75 sx 50/50 pozmix 4% gel. Plug down 6:00 AM. WOC

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Southwest Production Company

Address 162 Petr. Center Bldg.

Farmington, New Mexico

Original signed by
Carl W. Smith

By _____

Title Production Supt.