MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Po	ol	and b	U JSI.	^६ भटर		For	matio	n Plota	red Cl	1220		County	Sex	a Juna	1
In	Initial x Annual			Formation Plotumed Cliffs Special						Date of	Test	10/27/60			
Company Actor 611 and															
												78	To_	1806	
												2066			
Dat	e of Co	mple	tion:	10	la Ico		Packe	r		Single	-Brade	ell enhead-G. oir Temp.	G. or	G.O.	Dual
			<u>-</u>		Ha	<u> </u>	dene				eserv	oir Temp.		_	
Tes	ted Thr	ough	(Dmc	···	(() h = 1 =	- \	· · · · · · ·		VED DA	ľA					
	ted Thr	ougn				e) (1						Type Tal	os		
~	(Pro	ver)	(Ch	Flow I	Data Pre	ss.	Diff	Temp.		ing Da		Casing I		- -	
No.	(Li	ne)	(Ori	fice)	1	ł	J	•			•				Duration of Flow
Vor	Si	zе 	S	Size	ps	ig	h _w	°F.	psi	Lg	°F.	psig	[⊃] F•	_	Hr.
SI 1. 2.												53k			7 dage
2.			1		+							1.07	60(E)		here.
3.													 	+	
4.			 												
					+								<u> </u>	<u> </u>	
	Coef	fici	ent	1		Pres	I I I	LOW CAI	CULATI	ONS		10			
No.				 		11050	, an e	Fac	tor	Fa	avity	Compre	ss.	Rate	of Flow
	(21	-Hou	r)	$\sqrt{h_{W}}$	$p_{\mathbf{f}}$	psi	la	F	't	``	F _g _	Fpv			025 psia
1. 2. 3. 4. 5.	12.7.5			İ		110		1.0000		آروکی ا	1.01			33	
2.															
4.				 											
5.												 -			
							DDE	ecime o	A COUTY A	TONG					
							PRE	SSURE C	ALCULA	TIONS					
Gas L	iquid H	ydro	carbor	n Ratio	°			cf/bbl.			Specia	fic Gravi	ty Sepa	arator	Gas
sravı Es	ty of L	iqui	i Hydr	ocarbo '	ons 1 - e ^{-s}	7		deg.			Specia	fic Gravi	ty Flow	ving F	luid
				\	1-0						Pc	<u>546</u>	_ ^P c	298.1	16
							···								
No.	$P_{\mathbf{w}}$		Pt	· F	Q.	(F	_c Q) ²	(F	0,12		_	$P_c^2 - P_w^2$			
	Pt (ps	ia)	^ t	1 1	3	\1	CAN	(1)	_c Q) ² -e ^{-s})	P	w ²	$P_{c} - P_{\widetilde{\mathbf{w}}}$		l.	P _W P _C
1. 2.	119		11.16	7.	955	6.3	T .		70%	S R	- Y	11.	,	w	
3.		+				-									
4.						<u> </u>		+					 	_ _ -	
5.															
Absol COMP	lute Pom ANY	centi	al:		_15	33		MCFPD;	n	0.85					
ADDRI	ESS	Apto	•- 911	- au4 -9	ing G			Marris on							
	ACENT and TITLE ORIGINAL SIGNED BY L. M. STEVENS														
COMPA	ESSED	· -						_							
				<u>-</u>				REMA	RKS						
											70				
	SIPPLATE A														
	ुट्र 3 1 1990														
											ેC₃	3 T 33.W			
											OIL!	CON. COT			
											i	0151. 3	1		
												· · · · · · · · · · · · · · · · · · ·			

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt- Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

STATE OF NEV MEXICO										
OIL CORS RVATION COMMISSION										
AZE C DISTRICT OFFICE NUMBER OF COP ES RECEIVED D ST N										
									SANTA FE	
									FILS	
U.S.G.S.										
Lar D OFFIC.										
TRANSPORT, R GAS										
PROLATION OFFICE										
CPERA I OR										