

OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator Miridian oil. Inc. Lease Hanks Well No. 018
Location of Well: Unit B Sect. 5 Twp. 27N Rge. 9W County San Juan

	NAME OF RESERVOIR OR POOL	TYPE OF PROD. (Oil or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)
Upper Completion	<u>Pictured Cliffs</u>	<u>Gas</u>	<u>FLOW</u>	<u>Tbg.</u>
Lower Completion	<u>Dakota</u>	<u>Dead</u>	<u>FLOW</u>	<u>Dead</u>

PRE-FLOW SHUT-IN PRESSURE DATA

Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
	<u>3-8-96</u>	<u>5 days</u>	<u>224</u>	
Lower Completion	<u>3-8-96</u>		<u>2</u>	

FLOW TEST NO. 1

Commenced at (hour,date)* <u>3-13</u>		Zone producing (Upper or Lower) <u>Upper</u>			
TIME (hour,date)	LAPSED TIME SINCE*	PRESSURE		PROD. ZONE TEMP	REMARKS
		Upper Completion	Lower Completion		
<u>3-11</u>	<u>72 Hrs.</u>	<u>218</u>			<u>Dakota Dead</u>
<u>3-12</u>	<u>96 Hrs.</u>	<u>221</u>			
<u>3-13</u>	<u>120 Hrs</u>	<u>224</u>			<u>Turn on PC</u>
<u>3-14</u>	<u>144 Hrs.</u>	<u>142</u>			<u>PC. Run Test Back</u> <u>5:3.4 D5.0</u>
<u>3-15</u>	<u>168 Hrs</u>	<u>139</u>			<u>5 3.8 D3.5</u>

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hours. _____ Grav. _____ GOR _____

Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____

MID-TEST SHUT-IN PRESSURE DATA

Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)

(Continue on reverse side)

Page 2

[illegible]

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hours. _____ Grav. _____ GOR _____
 Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____
 Remarks: _____

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved Johnnie Robinson 19 Operator Meridian oil, Inc.
New Oil Conservation Division By Charles King
By MAY 5 1996 Title Operation Res.
Title DEPUTY OIL & GAS INSPECTOR Date 4-15-96

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be conducted on all multiple completions within seven days following recompletions and/or chemical or fracture treatments, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilizations. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
6. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1.

except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-scan tests must be measured on each scan with a nondescript pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil acre tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a downweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauges shall be required on the oil zone only, with downweight pressures as controls above being taken on the gas zone.

8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Asst. District Office of the New Mexico Oil Conservation Division of Northwest New Mexico District Leakage Test form Revised 10/01/78 with all deadweights pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).