

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
JUN 25 1993

OIL CON. DIV
DIST 3

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
790'FNL, 990'FEL Sec.4, T-27-N, R-9-W, NMPM

5. Lease Number
SF-078050

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Turner Hughes 6

9. API Well No.
30-045-

10. Field and Pool
S.Blanco PC

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

06-14-93 MOL&RU. TOOH w/tbg. Ran scraper to 2800'. Set cmt ret @ 2680'.

06-15-93 Sting out of ret, PT tbg 500#, ok. Sting in, east rate. Cmt plug #1 3010-2636', squeezed 80 sx Class "B" under ret, 5 sx above. Pull up to 2588'. Load hole w/ 50 BW. PT csg 500#, leaked 1/4 BPM. Spot 10 bbl 8.4# 40 vis mud 2588-2140'. LD 17 jts tbg. TOOH w/33 stds. Perf 4 holes @ 2140'. Load hole, est rate. Set cmt ret @ 2060'. Est rate. Cmt plug #2 2140-1778'. Squeeze 50 sx under ret, and 32 sx above. Pull to 1628'. Spot 16 bbl 8.4# 40 vis mud to 931'. Try to PT, leak @ 0.5 BPM @ 800#. TOOH. Perf 4 holes @ 931'. Set cmt ret @ 876'. Est rate. Cmt plug #3 931-805'. Squeeze w/39 sx below ret and 8 sx above. Spot 14 bbl 8.4# 40 vis mud 805-154'. TOOH. Perf 2 holes @ 154'. Squeeze 72 sx 154'-surface. Returns out bradenhead.

06-16-93 Cut off WH. Install dry hole marker. Released rig. Well plugged & abandoned.

14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs Date 6/17/93

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any: Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

APPROVED

JUN 22 1993
[Signature]
DISTRICT MANAGER

NMOCD

