Form 9-331a (Feb. 1951)

3

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa	. Fe	
Lease No. SI	r-0601	11	
Unit Gal	Legos	Canyon	Unit

SUNDRY NOTICES AND REPORTS ON WELLS

OTICE OF INTENTION TO DRILL	SUBSEQUENT H	REPORT OF WATER SHUT-OFF	
IOTICE OF INTENTION TO CHANGE ALANS		EPORT OF SHOOTING OR ACIDIZING	
IOTICE OF INTENTION TO TEST WATER SHUT-	▼	REPORT OF ALTERING CASING	1 1
IOTICE OF INTENTION TO RE-DRILL OR REPA		EPORT OF RE-DRILLING OR REPAIR	
IOTICE OF INTENTION TO SHOOT OR ACIDIZE	I I	REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CA	: II	RY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL	l II		
(INDICATE ABOV	E BY CHECK MARK NATURE OF REPORT,		
Gallegos Comyon Unit	Farmington	, New Mexico May 17	, 19. 61
ll No. 89 is located 9	90 ft. from Nine and	1650 ft. from W line of s	ec. 6.
NE/4 Mi/4 Section 6 T		н.м.р.м.	
(74 bee: and bee: 110)	(Twp.) (Range)	(Meridian)	
Basin Daketa (Field)	(County or Subdivision)	(State or Territory)	
The bedress and a control of the con	- 9 research Calains Cf	sing was set at 360' and	real marri
with 200 sacks containing	g 2 percent Calcium Gr	Moride, directived. A	es with t
. Ass and alex annies (mis	g 2 percent Calcium Gr	Moride, directived. A	es with a
with 200 sacks containing	g 2 percent Calcium Gr	500 pounds for 30 minutes 60' and continued drill	es with n
with 200 sacks containing	g 2 percent Calcium Gr	500 pounds for 30 minutes 60' and continued drill	es with n
with 200 sacks containing	g 2 percent Calcium Gr	Moride, directived. A	es with n
with 200 sacks containing on sement to set, tested drop in pressure. Reduc	g 2 percent Calcium Gr water shut off with f ed hole to 7-7/8" at 3	MAY 1 9 196	es with m
with 200 sacks containing on sement to set, tested drop in pressure. Reduce	g 2 percent Calcium Grant water shut off with sed hole to 7-7/8" at 3	MAY 1 9 196	on with E
with 200 sacks containing on sement to set, tested drop in pressure. Reduc	g 2 percent Calcium Grant water shut off with sed hole to 7-7/8" at 3	MAY 1 9 196	os with a
I understand that this plan of work must	g 2 percent Calcium Green water shut off with sed hole to 7-7/8" at 3	500 pounds for 30 minutes 60° and continued drill AFFFIV MAY 1 9 196	os with a
with 200 sacks containing on coment to set, tested drop in pressure. Reduce I understand that this plan of work must company Pan American Personal Pe	receive approval in writing by the Geol	MAY 1 9 196	os with a
Tunderstand that this plan of work must company Pan American Pedddress Box 480	receive approval in writing by the Geolegical Corporation When the corporation of the co	500 pounds for 30 minutes 60° and continued drill AFFFIV MAY 1 9 196	os with ling ope