

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

SF-046563

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

019 FARMINGTON, N.M.

7. Unit or CA, Agreement Designation

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

BRECK OPERATING CORPORATION

3. Address and Telephone No. c/o Walsh Engr. & Prod. Corp. 505 327-4892
204 N. Auburn Farmington, New Mexico 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit C, 790'FNL, 1750'FWL Section 2-T27N-R10W

8. Well Name and No.

Kutz Government #5

9. API Well No.

30-045 0693300

10. Field and Pool, or Exploratory Area

Fulcher Kutz PC

11. County or Parish, State

San Juan County, N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☒ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/13/92 Plug and Abandoned well as per attached.

RECEIVED

OCT 29 1992

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

OIL CON. DIV
DIST. 3

FOR: BRECK OPERATING CORPORATION

14. I hereby certify that the foregoing is true and correct

Paul C. Thompson, P.E.

Signed Paul C. Thompson

Title Agent

Date 10/16/92

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOC

AREA MANAGER

RECEIVED
BLM

92 OCT 20 PM 1:33

OIS FAX ALBUQUERQUE, N.M.

PLUG AND ABANDON

BRECK OPERATING CORPORATION
KUTZ GOVERNMENT #5
790'FNL, 1750'FWL, SECTION 2-T27N-R10W
San Juan County, New Mexico

- 10/13/92 Call BLM, Mark Kelly, at 0900 hrs. MOL and rig up A-Plus Well Service. ND wellhead and NU BOP. Pull donut and check for tubing. Tubing is 2-3/8" NUE, with turned down collars. SD for night.
- 10/14/92 TOH with 60 joints (1868') 2-3/8", NUE with buttress threads. TIH to 1868' and spot 20 sxs (24 cuft) plug (50' above top of PC with 100% excess). WOC 4 hrs. TIH to 1868' - did not tag plug. Pumped another 20 sxs (24 cuft). TOH and SD for night.
- 10/15/92 TIH and tag cement plug at 1520'KB. Load hole and pressure test to 600# - held okay. Spot 4 bbis of mud from 1520' to 1082'. TOH. Perf 4 holes at 1082'KB. Pumped 78 sxs (92 cuft) of cement down 3-1/2" tbg. Squeeze 64 sxs behind 5-1/2" casing and left 14 sxs in 3-1/2" - 50' above and below Ojo Alamo with 100% excess on outside and 50% excess inside 3-1/2". WOC. Tag plug at 740'. TIH to 691' KB and circ hole with 9.0 ppg mud. TOH laying down. Perf 4 holes at 137'. Est circ. Pumped 50 sxs (59 cuft) of cement and circulated to surface. ND BOP. Cut off wellhead and install P & A marker. Cement stub with 8 sxs. Job completed at 1600 hrs. 10/15/92.

Breck Operating
Kutz Government #5
NW/4 2 27N 10W
Plugged and Abandoned

RECEIVED
BLM

92 OCT 20 PM 1:33

019 FARMINGTON, N.M.

Installed P&A marker
Cement with 8 sx.

8-5/8"-24# K-55
set @ 106'
Cmt to surf
with 70 sx

9.0 ppg mud

Perfs @ 1082'

9.0 ppg mud

5-1/2" 14.0# K-55
set @ 1842'
Cement w/ 100 sx

3-1/2" @ 1904'
Cmt w/ 100 sx (circ.)
Open Hole TD 1943'

Perfs @ 137'
50 sx (59 cu.ft.)

TOC @ 740'

78 sx (92 cu.ft.)
(64 sx outside 5-1/2"
and 14 sx inside 3-1/2")

TOC @ 1331'

TOC @ 1520'

Spot two 20 sx
(24 cu.ft.) plugs
@ 1868'

PC perfs @
1862 - 1900'

Oct. 16, 1992

PCT