Form 3160-	1983)	UNITED STATES	SUBMIT IN TRI	ODE OD TO	Form approved. Budget Bureau N Expires August 3	1, 1985
(Formerly 9		TMENT OF THE INTI	E.T.IOT verse side)		5. LEASE DESIGNATION A	ND SERIAL NO.
	BUR	EAU OF LAND MANAGEM	<u>ENI</u>		SF 078566A	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					3. IF INDIAN, ALLOTTER (OR TRIBE NAME
OIL WELL	GAS TO OTHER		RECEI	VED	. UNIT AGREEMENT NAM!	<u> </u>
2. NAME OF	El Paso Natu	iral Gas Company	AUG 28 19	8	Howell	-
	PO Box 4289,	Farmington, NM	8.7499.	9	. WELL NO.	
f. LOCATION See also At surface	or WELL (Report location space 17 below.) ce	990'S, 1650'W	any FARMING FON RESOUR	CE AREA	O. FIELD AND POOL, OR S Blanco Mesa	
				1	1. SEC., T., R., M., OR RLE SURVEY OR ARTA Sec. 34, T-28	
14. PERMIT N	·0.	15. ELEVATIONS (Show whethe 5812		1:	2. COUNTY OF PARISH 1 San Juan	3. STATE NM
16.	Check A	Appropriate Box To Indicate	Nature of Notice, Rec	ort, or Othe	er Data	
	NOTICE OF INT		1		REPORT OF:	
PRACTUB	B ACIDIZE	MULTIPLE COMPLETE ABANDON® CHANGE PLANS	WATER SHCT-OFF FRACTURE TREATM SHOOTING OR ACID (Other) (Note: Repo	IZING DIT PROUTS OF	BEPAIRING WEL ALTERING CASIN ABANDONMENT* multiple completion on a Report and Log form.)	Well
	I'ROPUSED OR COMPLETED OF d work. If well is direct this work.) *	PERATIONS (Clearly state all pertinionally drilled, give subsurface lo	Sant date in the same		1.	
-						
8 -	Ran hole gils 2% c test orig	on location and 7" cement retaine with 100 sks. Conite, (180 cu.f. alcium chloride and casing to 1000 inal casing job stred. Did not square.	er, set @ 3632' lass "B" with 4 t.), followed b and 10% sand (6 D psi, ok. Ten showed Ojo Alan	Sque 1% gel, by 50 sk 52 cu.ft nperatur no forma	eze cemented 1/4 cu.ft. (s. Class "B' (s.). Pressure survey on ation to be	d open "with
8-	19-85 Dril	led out to 3742'.	. Ran knuckle	jt. and	l sidetracked	d
. 8-	23-85 Reac 10.5 4867 cu.f	Now drilling a hed TD of 4881'. #, K-55 casing, a '. Cemented with t. gilsonite, 0.0 of cement by tem	Logged well. 4868' set 0 488 1 150 sks. Clas 5% Halad-9 (270	Ran 12 30'. F1 3s "B" w) cu.ft.	oat collar s vith 4% gel,) WOC 18 ho	set at 1/4
8 -	24-85 PBTD	4867 Pressure	tested to 400	00 psi,	ok. Perf'd 4	1550',

PBTD 4867'. Pressure tested to 4000 psi, ok. Perf'd 4550',
4560', 4598', 4617', 4622', 4644', 4658', 4678', 4698',
4704', 4712', 4744', 4794', 4808' with 1 spz. Frac'd with
69,000# 20/40 sand and 87,060 gallons treated water.

Elushed with 3000 gallons.

SIONED LAGGE TOTE FEDERAL TITLE Drilling Clerk RECORD

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

TITLE Drilling Clerk RECORD

AUG 3 0 1935

FAKIMINGIUM RESOURCE ANEA

BY MATERIAL 29 1985

AUG 3 0 1935

See Instructions on Revolutions on Revolutions.

Title 18 U.S.C. Section 1001, makes it a crime for any person emotingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its missions.