


A blank grid paper with a bold 'X' mark in the second row from the top and the second column from the left.

LOCATE WELL CORRECTLY



U. S. LAND OFFICE **New Mexico**
SERIAL NUMBER **013363**
LEASE OR PERMIT TO PROSPECT

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

APR 21 1958

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

LOG OF OIL OR GAS WELL

Company El Paso Natural Gas Company Address Box 997, Farmington, New Mexico
Lessor or Tract Phillips Field So. Blanco P.C. Exp. State New Mexico
Well No. 2 Sec. 32 T. 28N R. 8W Meridian N.M.P.M. County San Juan
Location 1740 ft. XXX of N Line and 940 ft. E of W Line of Section 32 Elevation 6749

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed

Original Signed R. G. MILLER

Date November 18, 1958 Title Petroleum Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling 8-18-, 1958 Finished drilling 8-25- 19 58

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

(Delete gas by G)

No. 1, from <u>3009</u> to <u>3070 (G)</u>	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8 5/8"	24	8 Rd.	J-55	119'	Howco				Surface Prod. casing.
5 1/2"	15.5	8 Rd.	J-55	3109'	Baker				
1 1/4"	2.4	8 Rd.	Grade "A"	3044'					Siphon

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8 5/8"	129'	120	Circulated		
5 1/2"	3119'	200	Single Stage		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material..... Size

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from -----0----- feet to -----3122----- feet, and from ----- feet to ----- feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

-----~~9-8~~-----, 19~~58~~ Put to producing ----- 19-----

The production for the first 24 hours was ----- barrels of fluid of which -----% was oil; -----% emulsion; -----% water; and -----% sediment. Gravity. °Bé.

If gas well, cu. ft. per 24 hours 3,305,000 Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. ----- 845 ----- A.O.F.--3649 MCF/D

EMPLOYEES

_____, Driller

_____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	2069	2069	Tan to gry cr-grn ss interbedded w/gry sh.
2069	2186	117	Ojo Alamo ss. White cr-grn s.
2186	2710	524	Kirtland form. Gry sh interbedded w/tight gry fine-grn ss.
2710	3009	299	Fruitland form. Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.
3009	3070	61	Pictured Cliffs form. Gry, fine-grn, tight, varicolored soft ss.
3070	3122	52	Lewis formation. Gry to white dense sh w/silty to shaly ss breaks.

