Form 9-881 a. (Feb. 1951)					
	- 				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	S r
Lease No	078566
Unit	

NOTICE OF INTENT	TION TO DRILL		SUBSEQUENT	REPORT OF WATE		र ७ १९५	
4	TION TO CHANGE PLANS.		III	REPORT OF SHOO	1,000	103	
NOTICE OF INTENT	TION TO TEST WATER SHU	JT-OFF		REPORT OF ALTE		IZING	
NOTICE OF INTENT	TION TO RE-DRILL OR REI	PAIR WELL	III	REPORT OF RE-DI			
	TION TO SHOOT OR ACIDI		(1	REPORT OF ABAN			
NOTICE OF INTENT	TION TO PULL OR ALTER	CASING	ii ii	RY WELL HISTOR			
NOTICE OF INTENT	TION TO ABANDON WELL		Water Fr	BC.			X
	(INDICATE ABO	VE BY CHECK MARK	NATURE OF REPORT,	NOTICE, OR OTHE	ER DATA)		
				Septe	mber 30		19.57
ell No. 3(is located 1	050 ft. from	line and	950 ft. fi	rom 🎉 🗎 li:	na af eac	26
SW Sec.		28	EW	N.M.P.M	• ,	ne or sec	<u>e</u>
(1/2 Bec. and)			(Range)	(Meridian)			
KLANCO & i	South Blanco E		an Juan		Nev Mexi	.eo	
	of the derrick floor	DETAII	LS OF WORK	the of proposed or	(State or Terr	•	coment-
	expected depths to objecti	DETAII	el is 6110 f	the of proposed or		•	coment-
ate names of and e	expected depths to objection in Total depth	DETAII ive sands; show size ing points, and all ot \$955" • Flus	rel is 6110 fe LS OF WORK s, weights, and lengther important proper R back T. D.	ths of proposed ca	ssings; indicate	mudding jobs,	
ate names of and e	Total depth to objection for the second seco	DETAII ive sands; show size ing points, and all ot 1955 • Flue 192-40481 46	rel is 6110 fl LS OF WORK a, weights, and lengther important proper g back T. D.	ths of proposed co	wings; indicate Water fro Lone wate	emudding jobe, BCSQ - Fe BT and	L.
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000# sand.	DETAII ive sands; show size is points, and all of 1955 Plug 192-4648; 46 198 pr. 14	rel is 6110 fe LS OF WORK s, weights, and lengther important prope g back T. D. 354-45/6 w/6	ths of proposed colored work) 4899' 6,500 gal	water fr lons vat	emudding jobe, BCGQ - Fe BT BDQ - DT - 135	L.
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1	DETAII ive sands; show size ive points, and all of 1955' Plug 192-4646; 46 BD pr. 14 1506 IR 7	rel is 6110 fe LS OF WORK a, weights, and lengther important proper g back T. D. 654-46/6 w/6 400f, max. I	ths of proposed colored work) 4899' 5,500 gal r. 1400#,	water fr lons vat	emudding jobe, BCGQ - Fe BT BDQ - DT - 135	L.
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000 send. 1300, 1250, 1 sets of 20 be	DETAII ive sands; show size ing points, and all ot i955' Plug 192-4646; 46 PD pr. 14 1504 IR 7	rel is 6110 fe LS OF WORK a, weights, and lengther important proper g back T. D. 654-46/6 w/6 400f, max. I	ths of proposed colored work) 4899' 5,500 gal r. 1400#,	water fr lons vat	emudding jobe, BCGQ - Fe BT BDQ - DT - 135	L.
ate names of and e	Total depth to object in fortal depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth 4	DETAII ive sands; show size ing points, and all ot ing points, and a	rel is 6110 fe LS OF WORK a, weights, and long ther important prope g back T. D. 654-4676 w/6 400#, max. I 74.5 BPM. I or 4 stages.	the of proposed comed work) 4899'. 6,500 gal er. 1400#, lush 9,00	vater fr lons vate avg. tr 0 gallon:	emudding jobs, aced. F. er and e pr. 135 B. Dropp	L. O, ed 3
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to C. H. perf. i	DETAII ive sands; show size ing points, and all of 1955 Plug 192-4646; ix BD pr. 14 1504 IR 7 1115 each fo 1955 Temp int. 4206-42	rel is 6110 fe LS OF WORK a, weights, and lengther important prope g back T. D. 354-4676 w/6 4004, max. I 74.5 BPM. I 74.5 BPM. I 74.5 BPM. I 2221 k248-42	ths of proposed colored work) 4899' 6,500 gallor, 1400#, lush 9,00 ps plug at	water from water avg. tr 0 gallon: 4500'.	emudding jobs, aced. F. er end e pr. 135 E. Dropp Water fr	L. O, ed 3 aced.
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000 send. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 send.	DETAII ive sands; show size ive points, and all of 1955'. Plug 192-4646; 46 206-18 206-18 206-42 20 pr. 17	rel is 6110 fe LS OF WORK s, weights, and lengther important prope g back T. D. 654-46/6 w/6 400#, max. I 74.5 BPM. II or 4 stages. porary bridg 22; 4248-42	ths of proposed colored work) 4899'. 6,500 gal. 7. 1400#, Tush 9,00 p plug at 90 v/63,90	water from water from water from water from water avg. tr. 0 gallons 4500°.	mudding jobs, aced. F. er end . pr. 135 s. Dropp Water fr ns water (L. O, ed 3 sced. and
ate names of and e	Total depth to object in Total depth to perf. int. 47 60,000# sand. 1300, 1250, 1 sets of 20 be Total Depth to C. H. perf. i 60,000# sand. 2000#. IR 56	DETAIL ive sands; show size ing points, and all of 1955' Flug 192-4040; 46 RD pr. 14 150% IR 7 1150% Teng nt. 4206-42 ED pr. 17	rel is 6110 fe LS OF WORK s, weights, and lengther important prope g back T. D. 654-46/6 w/6 400#, max. I 74.5 BPM. II or 4 stages. porary bridg 22; 4248-42	ths of proposed colored work) 4899'. 6,500 gal. 7. 1400#, Tush 9,00 p plug at 90 v/63,90	water from water from water from water from water avg. tr. 0 gallons 4500°.	mudding jobs, aced. F. er end . pr. 135 s. Dropp Water fr ns water (L. O, ed 3 sced. and
ate names of and e 9-24-57	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to C. H. perf. i 60,000 sand. 2000 IR 56 for 3 stages.	DETAII ive sands; show size ive points, and all of 1955'. Plug (92-4646; 46 . RD pr. 14 150%. IR 7 1118 each fo 1955'. Temp int. 4206-42 . RD pr. 17 15 EFM. F1	rel is 6110 fe LS OF WORK a, weights, and long ther important prope g back T. D. 654-4676 w/6 400#, max. I 74.5 BPM. I or 4 stages. porary bridg 222; \$248-42 700#, max. P tush 7000 ga	ths of proposed colored work) 4899'. 6,500 gal. 7. 1400#, Tush 9,00 p plug at 90 v/63,90 r. 2100#, llons. Di	water from water from water from water from the wat	emudding jobs, aced. F. er and e pr. 135 b. Dropp Water from water (pr. 175) acts of (L. O, ed 3 aced. and O, 185 L8 bal
ate names of and e 9-24-57	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 IR 56 for 3 stages. Total depth to	DETAII ive sands; show size ing points, and all of 1955' Plug 192-4646; 46 RD pr. 11 150# IR 7 1118 each fo 1955' Temp 15 RFM. Pl 1955. Temp 1955. Temp	rel is 6110 for LS OF WORK was weighte, and lengther important property back T. D. 654-4676 w/6 400%, max. If the stages were bridge 22; \$248-42 100%, max. If the stages were bridge over bridge.	the of proposed colored work 4899'. 6,500 galler. 1400#, Tush 9,00 plug at 90 v/63,90 r. 2100#, 11ons. Di	Water from water avg. tr 0 gallon: 4500'. 00 gallon: evg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from pr. 175 sets of	L. 0, ed 3 eced. end 0, 185 18 bal
ate names of and e 9-24-57 9-24-57	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25	DETAIL ive sands; show size ing points, and all of 1955' Flug 192-4048; 46 RD pr. 11 150# IR 7 1118 each for 1955' Tempo 15 EFM. F1	rel is 6110 fe LS OF WORK a, weights, and lengther important property g back T. D. 654-4676 v/6 400#, max. If 74.5 BPM. If or 4 stages. porary bridge 122; 4248-42 700#, max. p ush 7000 ga	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water from water 1500°. 1500° allow avg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from water (pr. 175) acts of (acts from the following section (acts from the following se	L. O, ed 3 aced. and O, 185 18 bal
ate names of and e 9-24-57 9-24-57	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25	DETAIL ive sands; show size ing points, and all of 1955' Flug 192-4048; 46 RD pr. 11 150# IR 7 1118 each for 1955' Tempo 15 EFM. F1	rel is 6110 fe LS OF WORK a, weights, and lengther important property g back T. D. 654-4676 v/6 400#, max. If 74.5 BPM. If or 4 stages. porary bridge 122; 4248-42 700#, max. p ush 7000 ga	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water from water 1500°. 1500° allow avg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from water (pr. 175) acts of (acts from the following section (acts from the following se	L. O, ed 3 aced. and O, 185 18 bal
24-57 -24-57 understand that	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must reflush 5000 ga	DETAII ive sands; show size ive points, and all of 1955' Plug (92-4646; 46 RD pr. 14 1506' IR 7 11506' Tempo 10-2533; 25 110-2533; 25 110-2533; 25	rel is 6110 fe LS OF WORK a, weights, and lengther important property g back T. D. 654-4676 v/6 400#, max. If 74.5 BPM. If or 4 stages. porary bridge 122; 4248-42 700#, max. p ush 7000 ga	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water from water 1500°. 1500° allow avg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from water (pr. 175) acts of (acts from the following section (acts from the following se	L. O, ed 3 aced. and O, 185 18 bal
ate names of and e 9-24-57 9-24-57 1-24-57	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25 BB. pr. 2450 for 3 stages.	DETAII ive sands; show size ive points, and all of 1955' Plug (92-4646; 46 RD pr. 14 1506' IR 7 11506' Tempo 10-2533; 25 110-2533; 25 110-2533; 25	rel is 6110 fe LS OF WORK a, weights, and lengther important property g back T. D. 654-4676 v/6 400#, max. If 74.5 BPM. If or 4 stages. porary bridge 122; 4248-42 700#, max. p ush 7000 ga	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water from water 1500°. 1500° allow avg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from water (pr. 175) acts of (acts from the control of the	L. O, ed 3 aced. and O, 185 18 bal
24-57 24-57 1 understand that	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to th	DETAII ive sands; show size ive points, and all of 1955' Plug (92-4646; 46 RD pr. 14 1506' IR 7 11506' Tempo 10-2533; 25 110-2533; 25 110-2533; 25	rel is 6110 fe LS OF WORK a, weights, and lengther important property g back T. D. 654-4676 v/6 400#, max. If 74.5 BPM. If or 4 stages. porary bridge 122; 4248-42 700#, max. p ush 7000 ga	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water from water 1500°. 1500° allow avg. tr. ropped 2	mudding jobs, aced. F. er end pr. 135 Dropp Water from water (pr. 175) acts of (acts from the control of the	L. O, ed 3 aced. and O, 185 18 bal
24-57 24-57 1 understand that	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to th	DETAII ive sands; show size ive points, and all of 1955' Plug (92-4646; 46 RD pr. 14 1506' IR 7 11506' Tempo 10-2533; 25 110-2533; 25 110-2533; 25	rel is 6110 for LS OF WORK as, weights, and lengther important property by 650-4676 v/6 100%, max. If the stages are the stage	the of proposed colored work) 4899' 6,500 gallor. 1400#, lush 9,00 s plug at 90 v/63,9 r. 2100#, llons. Dr plug at 9,800 gall tr. pr.	Water from water from water from water from water 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°.	water fraces 40,000 IR	L. O, ed 3 aced. and O, 185 18 bal
24-57 -24-57 understand that mpany El P	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 IR 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must be Flush 5000 gas aso Natural Gas 997	DETAII ive sands; show size by points, and all of 1955'. Plug (92-4648; 46 BD pr. 14 150#. IR 7 1150#. Temp int. 4206-42 BD pr. 17 55 EFM. F1 1955. Temp 10-2533; 25 , max. pr. 11cns. Dro s Company	rel is 6110 for LS OF WORK as, weights, and lengther important property by 650-4676 v/6 100%, max. If the stages are the stage	the of proposed colored work) 4899' 6,500 gallor. 1400#, lush 9,00 s plug at 90 v/63,9 r. 2100#, llons. Dr plug at 9,800 gall tr. pr.	Water from water from water from water from water 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°.	water fraces 40,000 IR	L. O, ed 3 aced. and O, 185 18 bal
24-57 Lunderstand that mpany El P BOX dress BOX	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 In 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to the perf. int. 25 BD. pr. 2450 this plan of work must related to th	DETAII ive sands; show size by points, and all of 1955'. Plug (92-4648; 46 BD pr. 14 150#. IR 7 1150#. Temp int. 4206-42 BD pr. 17 55 EFM. F1 1955. Temp 10-2533; 25 , max. pr. 11cns. Dro s Company	rel is 6110 for LS OF WORK as, weights, and lengther important property by 650-4676 v/6 100%, max. If the stages are the stage	the of proposed colored work) 4899' 6,500 galler. 1400#, lush 9,00 s plug at 90 v/63,96 r. 2100#, llons. Di plug at	Water from water from water from water from water 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 1500°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°. 150°.	water fraces 40,000 IR	L. O, ed 3 aced. and O, 185 18 bal
24-57 1 understand that ompany E1 P dress Box	Total depth to object in Total depth to perf. int. 47 60,000 sand. 1300, 1250, 1 sets of 20 be Total Depth to 60,000 sand. 2000 IR 56 for 3 stages. Total depth to perf. int. 25 BD. pr. 2450 this plan of work must be Flush 5000 gas aso Natural Gas 997	DETAII ive sands; show size by points, and all of 1955'. Plug (92-4648; 46 BD pr. 14 150#. IR 7 1150#. Temp int. 4206-42 BD pr. 17 55 EFM. F1 1955. Temp 10-2533; 25 , max. pr. 11cns. Dro s Company	rel is 6110 fe LS OF WORK a, weights, and lengther important proper g back T. D. 354-45/6 w/6 400#, max. I 74.5 BPM. I or 4 stages. porary bridge 222; \$248-42 700#, max. p ush 7000 ga prary bridge 550-2565 v/3 2450#, avg. riting by the Geolog pped one se	the of proposed colored work) 4899' 6,500 gallor. 1400#, lush 9,00 s plug at 90 v/63,9 r. 2100#, llons. Dr plug at 9,800 gall tr. pr.	water from water from water from water from water to gallon water to gallon water to water to gallo for Signed D	water fraces 40,000 IR	L. O, ed 3 aced. and O, 185 18 bal