

## 1300000 NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410

OCT 2000 (505) 334-6178 FAX: (505) 334-6170 http://emnrd.state.nm.us/ocd/District ill/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

Amo Operator 20	<b>NC</b> oco Production O Amoco Court	n Company			R-LEAKAGE TES	T Well No _ 3	
					<u>W</u> API#30-0 <u>'45-</u> (		
	NAME OF RESE	RVOIR OR POOL		F PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)	
Upper Completion	S Blan	co PC	GAS	S	FLOW	TBG	
Lower Completion	Blanca		GAS	S	FLOW	TBG	
		PRE	-FLOW SHUT-I	N PRESSUR	E DATA		
Upper	Hour, date shut-in		Length of time		SI press. Psig	Stabilized? (Yes or No)	
Completion	10/19/00		72 HOU		140	YES	
Lower Completion	Hour, date shut-in		Length of time:		SI press. Psig	Stabilized? (Yes or No) YES	
Completion	10/19	/00	FLOW TE		191	123	
Commenced at (	(hour, date)*			i	(Upper or Lower):		
TIME (hour,date)	LAPSED TIME SINCE*	PRESSURE		PROD. ZON	IE REMARKS		
		Upper Completion	Lower Completion	TEMP.			
10/19	DAY 1	129	194		BOTH ZONES	SHUT IN	
10/20	DAY 2	134	245		BOTH ZONES		
10/21	DAY 3	138	259		BOTH ZONES SHUT IN		
10 /aa_	DAY 4	140	191		FLOW Lower ZONE		
lo/23	DAY 5	142	134		FLOW "	ZONE	
10/24	DAY 6	148	133		FLOW "	ZONE	
roduction ra	te during test	·					
il:		d on	nBbls. inHoursGra		ravGOR		
as:		MCF	PD; Tested thru	(Orifice or M	eter):		
		MID	-TEST SHUT-IN	PRESSURE	DATA		
Upper Completion	Hour, date shut-in		Length of time s		SI press psig	Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in		Length of time s	hut-in	SI press. psig	Stabilized? (Yes or No.)	

(Continue on reverse side)

## FLOW TEST NO. 2

Commence	d at (hour, date)*	na.		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	R	EMARKS		
	te during test	based onMCFF	Bbls D:Tested thru (C	. inHour	sGrav	GOR		
			tained is true and		bes of my knowledg			
Approved		3 200 <b>0 <sub>19</sub></b>			duction Compan			
CHICHNA	ar <b>alomed</b> sa ch	in a succession of the success			idshaw 🚱			
		rbaok der 🚜			/00			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).