

& NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-6178 FAX: (505) 334-6171

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

Lower Completion Blanco

Page Revised 11/16/9

TBG

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

bp America Production Company

Operator 200 Energy Ct, Farmington Lease Name To receive Well No (a)

Location of Well:Unit Letter L Sec 30 Twp 2 8 N Rge 8 W API # 30-0'45-07 1 35

NAME OF RESERVOIR OR POOL TYPE OF PROD. (Oil or Gas) (Flow or Art. Lift) PROD.MEDIUM (Tbg. or Csg.)

Upper GAS FLOW TBG

PRE-FLOW SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press. Psig Length of time shut-in Hour, date shut-in Upper **72 HOURS** Completion Stabilized? (Yes or No) Length of time shut-in SI press. Psig Lower 72 HOURS YES 243 Completion

FLOW TEST NO. 1

GAS

FLOW

Zone producing (Upper or Lower): Commenced at (hour, date)* REMARKS PROD. ZONE PRESSURE LAPSED TIME TIME TEMP. SINCE* (hour,date) Upper Completion Lower Completion 25 234 BOTH ZONES SHUT IN 187 DAY 1 BOTH ZONES SHUT IN 189 238 26 DAY_2 BOTH ZONES SHUT IN 191 ユサス DAY 3 27 FLOW Lower ZONE 23028 DAY 4 192 180 ZONE 194 FLOW DAY 5. 1.29 11 ZONE 95 FLOW 6 30 DAY 6

Oil:______BOPD based on_____Bbls. in___Hours___Grav.___GOR____

Gas:______MCFPD; Tested thru (Orifice or Meter):______

MID-TEST SHUT-IN PRESSURE DATA

 Upper Completion
 Hour, date shut-in
 Length of time shut-in
 SI press psig
 Stabilized? (Yes or No)

 Lower Completion
 Hour, date shut-in
 Length of time shut-in
 SI press. psig
 Stabilized? (Yes or No)

(Continue on reverse side)

FLOW TEST NO. 2

Commence	Commenced at (hour, date)**				Zone producing (Upper or Lowr):	
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS	
						·
Jas	BOPD &	NICFPL	J. i estea thru (Or	Tice or Meter):	GravGOR	
hereby certify	that the informa	ation herein cont	ained is true and	complete to the bes of	my knowledge	_
exico Oil Conservation Division			Amoco Production Company Sheri Bradshaw		_	
OPROBLAL SA	BINED BY CHARFT	S T. PERFEN				-
itle	GIL & SAS INSPE	CTOR, MST. #8				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the weilhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which ν previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadwein pressure gauge at time intervals as follows: 3 hours tests: immediately prior to beginning of each flow-period, at fifteen-minute intervals during the first hour there and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period; at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall continuously measured and recorded with recording pressure gauges the accura of which must be checked at least twice, once at the beginning and once at the ϵ of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil- ϵ dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 de after completion of the test. Tests shall be filed with the Aztec District Office of t New Mexico oil Conservation Division on northwest new Mexico packer leakage Tr Form Revised 11-16-98 with all deadweight pressures indicated thereon as well the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)