

Form 9-331a  
(March 1942)

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078363  
Unit Graveling

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 22, 1951

Well No. 3-A is located 1650 ft. from N line and 1650 ft. from E line of sec. 23

22 NE Section 20 23N 6W N. H. P. M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Large Est. San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5049 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

March 20, 1951:

Set 7" casing at 3317' using 640' of 23 lb. N-80 on bottom, and 3184' of 20 lb. J-55 on top. Cemented with two stages:

First stage - Used 130 sacks Ideal Regular. Top by Temperature Survey was 2990'.

Second Stage - (Took at 2459') used 200 sacks Ideal Regular and 10 sacks of Strata Seal. Top of cement by Temperature Survey was 1785'.

Held 600 lbs. for 10 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SAN JUAN PRODUCTION COMPANY

Address 1001 North Court Avenue

Farmington, New Mexico

By E. J. Coel

Title Petroleum Engineer