

HEW MEALOU ENERGY, MINTERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-6176 FAX: (505) 334-6170 d.state.nm.us/ocd/District NV3die

Stabilized? (Yes or No.)

Stabilized? (Yes or No)

Page Revised 11/16/9

This form is not to be used for reporting packer leakage tests In Southeast New Mexico

Hour, date shut-in

Hour, date shut-in

Upper

Completion

Lower

Completion

NORTHWEST NEW MEXICO PACKER-I bp America Production Company 200 Energy Ct, Farmingto Lease Name Well No 4 Location of Well:Unit Letter B Sec 29 Twp 28 N Rge 8 W API # 30-0145- 07186 NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD.MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper GAS Completion lanco FLOW TBG 'GAS FLOW TBG M Completion PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in SI press. Psig Stabilized? (Yes or No) Upper Completion 72 HOURS YES Length of time shut-in SI press. Psig Stabilized? (Yes or No) Lower 72 HOURS Completion 226 YES **FLOW TEST NO. 1** Commenced at (hour, date)* Zone producing (Upper or Lower): LAPSED TIME PRESSURE TIME PROD. ZONE REMARKS SINCE* (hour,date) TEMP. **Upper Completion Lower Completion** 25 DAY 1 199 219 BOTH ZONES SHUT IN **ವಿ**ನಿ ಇ 6 26 ಎ೦5 DAY 2 BOTH ZONES SHUT IN 27 DAY 3 BOTH ZONES SHUT IN 28 DAY 4 FLOW 1 owe/ ZONE DAY 5 29 FLOW ZONE 6 30 186 DAY 6 FLOW ZONE Production rate during test BOPD based on _____Bbls. in____Hours____Grav.___GOR Oil: _MCFPD; Tested thru (Orifice or Meter): Gas: MID-TEST SHUT-IN PRESSURE DATA

(Continue on reverse side)

Length of time shut-in

Length of time shut-in

SI press psig

SI press, psig

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**	PRESSUF Upper Completion 1		PROD. ZONE	RI	EMARKS
roduction rat	_					
il: as:	BOPD	based on MCFPD:	Bbls. Tested thru (O	inHours fice or Meter):	sGrav	GOR
emarks:		· · · · · · · · · · · · · · · · · · ·			·	
	4.			•	bes of my knowledge	
p proved exico Oil Cons	ervation Division	<u> 2002</u> 19	-		duction Company	
OPIGINAL	Signaed by Chap	LET POMBIN	By	Sheri Bra	dshaw SB	
Y			Title_	Field Tecl	h	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the weilhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which ν previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadwoi pressure gauge at time intervals as follows: 3 hours tests: Immediately prior to beginning of each flow-period, at fifteen-minute intervals during the first hour there and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow per (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall continuously measured and recorded with recording pressure gauges the accurr of which must be checked at least twice, once at the beginning and once at the ϵ of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil- ϵ dual completion, the recording gauge shall be required on the oil zone only, w deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 da after completion of the test. Tests shall be filed with the Aztec District Office of t New Mexico oil Conservation Division on northwest new Mexico packer leakage Ti Form Revised 11-16-98 with all deadweight pressures indicated thereon as well the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)