## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES  DEPARTMENT OF THE INTERIOR	5. LEASE NM-03549
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME Florance C
1. oil gas Mell other	9. WELL NO.
2. NAME OF OPERATOR Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Box 3249 Englewood, Colorado 80155	Basin Dakota  11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	AREA Sec 19 T28N R8W
below.) AT SURFACE: 950' FSL 1650' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH:  15 CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	14. API NO.
TE CHECK APPROPRIATE BOX TO INDICATE MATORE OF HOTOE	· · · · · · · · · · · · · · · · · · ·

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON\* (other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5784' gr

3/3/81. Tenneco has plugged and abandoned the above referenced well, as follows; Squeezed Dakota perfs from 6470-6500' w/100sx cmt. Squeezed Point Lookout perfs @ 4550' w/50sx cmt. Set a 115sx cmt plug from 4450-3600'. Set a 25sk cmt plug from 2030-2250'. Perforated @ 526'. Circ 175 sx cmt to surface. Set a 100 sk cmt plug @ surface. Cut off well head. Install P & A marker. RDMDSU.

SUBSEQUENT REPORT OF:

Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct April 7, 1981 Asst.Div.Adm.Mgr. DATE TITLE (This space for Federal or State office use) TITLE AS AMENL APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

\*See Instructions on Reverse Side

JAN 1 0 1935 LBL J. Stan McKe. M. MILLENBACH AREA MANAGER