

**(SUBMIT IN TRIPLICATE)**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**Land Office** -----

Lease No. 1000

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

\_\_\_\_\_, 19\_\_

Well No. 3 is located 220 ft. from N line and 240 ft. from E line of sec. 10

(1/4 Sec. and Sec. No.)      (Twp.)      (Range)      (Meridian)  
 (Field)      (County or Subdivision)      (State or Territory)

The elevation of the derrick floor above sea level is 510 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Local approval given April 15, 1942.  
Above well was drilled to pictured point, Total depth 2110'. Pictured point  
was 2000' point.  
Flagged for gas purposes and connected to water well in the following manner:  
1. 1/2 inch cement plug placed at the bottom of the 5 1/2" pipe, shot well  
succeeded as much as possible. Hole raised up to 600' below water level.  
2. 3/4 inch cement plug. Top of the plug at 2050'.  
2710' of 5 1/2" removed.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company \_\_\_\_\_

Address \_\_\_\_\_

**Figure 1**

By \_\_\_\_\_

**Title** \_\_\_\_\_