

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or recomplete a well in a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals

RECEIVED  
BLM  
96 JUL 30 AM 11:03  
070 FARMINGTON, NM

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Amoco Production Company

3. Address and Telephone No.

Attention:  
Pat Archuleta, Room 1205C

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

890' FSL 1140'FWL Sec. 23 T 28N R 8W Unit M

5. Lease Designation and Serial No.

NM-013860

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Russell LS 3

9. API Well No.

3004507242

10. Field and Pool, or Exploratory Area

Blanco Mesaverde/So. Blanco Pict.

11. County or Parish, State

San Juan New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Downhole Commingle

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths of perforations and zones pertinent to this work.)

MIRUSU 7/10/96.

Ran casing scraper to 4600'. Set RBP over Mesaverde perms at 4500', tested plug and 4.5 casing, dumped sand on RBP.

Set packer in top of liner at 2450', tested to 1000#, held okay. Ran CBL to liner top 2400', isolation good.

Limited entry perforations in Mesaverde: 4009', 4023', 4039', 4046', 4049', 4059', 4063', 4073', 4086', 4090', 4094',

4285', 4397', w/ 1 jsfp, .340 inch diameter total 14 shots fired. Acidize 4009'-4397' with 12 bbls acid, max pressure 3000 psi, max rate 5.9 BPM. Break down perfor. Frac'd 4009'-4397' with 530 bbls water and 779,060 scf of N2 to create a 70% quality foam along with 73,087 lbs of 16/30 Arizona Sand, flowing well. Cleaned sand off RBP at 4500', tagged fill with N2 to 4756', land tubing at 4690'.

RDMOWU 7/17/96.

RECEIVED  
AUG - 5 1996

OIL CON. DIV.  
BMT 3

14. I hereby certify that the foregoing is true and correct

Signed

*Pat Archuleta*

Title

Clerk

Date

07-29-1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

ACCEPTED FOR RECORD

JUL 31 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

U/MOCD

See Instructions on Reverse Side

FARMINGTON DISTRICT OFFICE

2V 22