



(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 101-04208
Unit Sec. 14

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 2, 1960

Well No. 1 is located 1800 ft. from N line and 1800 ft. from E line of sec. 14
Sec. 14 26-4 9-4 121N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Unden, Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the Unden G. L. 3950 ft.
~~Unden G. L.~~

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

After setting 8-5/8" casing, a 7-7/8" hole was drilled to 6910' T.D. w/mud. 5-1/2" 17# J-55 casing set at 6910' w/D.V. tool at 2403'. Cemented lower stage w/150 axs. 50/50 Pozumix 41 Gel. A 12-1/2# Gilsomite per ax. followed w/45 axs later cement. Good returns during cement job & casing pressured to 3000# for 1 hr. w/no drop in pressure. Temp. survey indicated top @ 3300'. Cemented upper stage w/100 axs. cement, 41 Gel. casing pressured to 3000# and held. Temp. survey indicated top at 2100'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Calhi-Taylor Oil Corporation

Address P. O. Drawer 1198

Permington, New Mexico

By J. E. Howell
Dist. Supt.

Title