

& NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 [505] 334-6178 FAX: (505) 334-6170 mnrd.state.nm.us/ocd/District HV3disi

Stabilized? (Yes or No)

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Hour, date shut-in

Lower Completion JUL 2002 RECEIVED W CONS. DN.

Page : Revised 11/16/9

NORTHWEST NEW MEXICO PACKER LEAKAGE EST

	bp America 200 Energy			ıme Mc	Cullery	Well No <u>-</u>		
Location of	f Well:Unit Lette	r <u> </u>	14 Twp 28	<u>∖N</u> Rge <u></u>	W API # 30-0'45-	07443		
	NAME OF RESERVOIR OR POOL			OF PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	Aztec	PC.	GA	s	FLOW	TBG		
Lower Completion	Blance		GA	S	FLOW	TBG		
			-FLOW SHUT-	N PRESSUR	E DATA			
Upper Hour, date shut-in			Length of time		SI press. Psig	Stabilized? (Yes or No)		
Completion	Hour, date shuf-in		72 HO		199	YES		
Lower	1		Length of time		SI press. Psig	Stabilized? (Yes or No)		
Completion	6/25/02		72 HO	ST NO. 1	239	YES		
Commenced at	(hour, date)*	····	FLOVAIR	T	(Upper or Lower):			
TIME	LAPSED TIME	PRESSURE		PROD. ZONI	E REMARKS			
(hour,date)	SINCE*	Upper Completion	Lower Completion	TEMP.				
6 / 25	DAY 1	115	303		BOTH ZONES	BOTH ZONES SHUT IN		
6 / 26	DAY 2	119	226			BOTH ZONES SHUT IN		
5 / 27	DAY 3	122	239			BOTH ZONES SHUT IN		
6 / 28	DAY 4	124	195		FLOW Lowe			
6 /:29	DAY 5	127	149		FLOW "	ZONE		
6 / 30	DAY 6	129	109		FLOW "	ZONE		
roduction ra	te during test							
il:BOPD based on			d on	Bbls. in	HoursG	ravGOR		
as:		MCF	PD; Tested thru	(Orifice or Me	eter):			
		MID	-TEST SHUT-IN	PRESSURE	DATA			
	Hour, date shut-in		Length of time s		SI press psig	Stabilized? (Yes or No.)		

(Continue on reverse side)

SI press. psig

Length of time shut-in

1

Commenced at (hour, date)\*\*\*

TIME (hour, date)

Since\*\*\*

PRESSURE Upper Completion Lower Completion

PROD. ZONE

REMARKS

Production rate during test

Oil:	BOPD based on	Bbls. ir	1Hours	Grav.	GOR_					
Gas:	Gas: MCFPD:Tested thru (Orfice or Meter):									
Remarks:										
I hereby certify that	the information herein cont	ained is true and o	complete to the bes of	of my knowledg	je.					
Approved	19	Operator	Amoco Product	tion Compan	<u>y</u> New					
Mexico Oil Conservat		D.,	Chaud Duadata	. 92						
OPERMAL SIGN	RED SOY SHAPPLIE T. PREPARE	Ву	Sheri Bradsha	W 00	<del></del>					
By	L & GAS INSPECTOR, INST. 46	Title	Field Tech							
Title	- and martin, Mil.	Date	7/3/02							

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the weilhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which vipreviously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadwein pressure gauge at time intervals as follows: 3 hours tests: Immediately prior to beginning of each flow-period, at lifteen-minute intervals during the first hour there and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period; and immediately prior to the conclusion of exflow period. Other pressures may be taken as desired, or may be requested wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall continuously measured and recorded with recording pressure gauges the accurs of which must be checked at least twice, once at the beginning and once at the  $\epsilon$  of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil- $\epsilon$  dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 da after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage To Form Revised 11-16-98 with all deadweight pressures indicated thereon as well the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).