

(SUBMIT IN TRIPLICATE)


Land Office

01772-A

Lease No.

Brid

Unit

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. \_\_\_\_\_ is located 1430 ft. from N line and 921 ft. from W line  
SW Sec. 8 22N 9E N.H.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Blanco N.V. San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6018 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud date 6-15-58.

On 6-17-58. Total Depth 174'.

Run 4 joints 10 3/4", 32.75#, spiral weld casing (161') set at 174' with 150 sacks regular cement circulated to surface.

Held 500# for 30 minutes.

On 6-21-58. Total Depth 2457'.

Run 75 joints 7 5/8", 26.40#, casing (2446') set at 2457' with 75 sacks regular cement, 75 sacks Pozmix, 37# Floccule and 25 gal. followed w/50 sacks Best cement. Held 1000# for 30 minutes.

Top of cement by temperature survey at 1320'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas CompanyAddress Box 997Farmington, New MexicoBy Original Signed D. C. JohnstonTitle Petroleum Engineer