

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424
5. LEASE DESIGNATION AND SERIAL NO.I-89-IND-57
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. UNIT AGREEMENT NAME Navajo TRIBE
2. NAME OF OPERATOR JOHN F. STAVCR	8. FARM OR LEASE NAME Table MCSA
3. ADDRESS OF OPERATOR Box 51 Farmington, New Mexico	9. WELL NO. 29
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1850 FNL, 790 FEL	10. FIELD AND POOL, OR WILDCAT Table MCSA - MISSISSIPPI PENN
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5324 GR.
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 9 T27N R17W NMPM
	12. COUNTY OR PARISH SAN JUAN
	13. STATE N. MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose To plug AND ABANDON THIS WELL STARTING MAY 18, 1974
TOPS ARE AS FOLLOWS: GALLUP 470 - DAKOTA 1352 - MORRISON 1540 -
ENTRADA 2600 - De Chelly 4109 - HERMOSA 5982 - PARDON 6593 -
MISSISSIPPI 7385 - DEVONIA 7535 - WAS COMPLETED OPEN HOLE 7380 -
TO 7533' - 4" LINER SET AT 7800' CEMENT CIRCULATED AND PLUG 7498-7502
IN MISS. 5 1/2" CASING 17" N-80 SET @ 7380' 150 SKS. CEMENT TOP 6660'
PERFORATIONS 7037' TO 7042'. 9 5/8" CASING 40" N-80 SET @ 5025'
WITH 225 SKS. STAGE COLLAR @ 1580 WITH 100 SKS. 13 7/8" CASING 48" SET
@ 503' CEMENT CIRCULATED.

Propose To RUN 2 3/8" TUBING TO SPOT BOTTOM PLUGS - PULL 2 3/8"
TUBING AND 5 1/2" CASING - SETTING PLUGS AS DIRECTED - ERRECT DRY
HOLE MARKER AND CLEAN LOCATION - Plugging Sequence T.D 7533' To 7000'
6250' - 6350' bottom 5 1/2" csg - 5907' - 6057' HERMOSA - 75' 5050' -
Base 9 5/8" - 100' De Chelly 4050' - 4150' - 75' SURFACE
Mud between Plugs

18. I hereby certify that the foregoing is true and correct

SIGNED

John Cunningham

TITLE

Manager

DATE

May 13, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side