

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

JUL 02 1985

5. LEASE DESIGNATION AND SERIAL NO.

0200000000

SF-078902

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.

247

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

NE/4 Sec5, T27N, R12W

12. COUNTY OR PARISH

13. STATE

San Juan

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5705' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

1. SHUT OFF

2. REFRAT

3. SHOOT OR ACIDIZE

4. REPAIR WELL

(Other)

5. MULTIPLE COMPLETE

6. ABANDON*

7. CHANGE PLANE

8. REFRAT

9. FRACTURE TREATMENT

10. SHOOTING OR ACIDIZING

(Other)

11. REPAIRING WELL

12. ALTERING CASING

13. ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

Moved in and rigged up service unit on 5-2-85. Total depth of the well is 6018' and plugback depth is 5984'. Perforated the following intervals: 5872'-5890', 5936'-5960', 2 jsp, .50" in diameter, for a total of 84 holes. Fraced interval 5872'-5960' with 85,000 gal 70 quality foam and 105,000 # mesh brady sand. Hydro tested tubing to 4000 psi for 30 minutes. Cleaned out 54' of fill with nitrogen foam. Cleaned out 20' of fill with nitrogen foam. Cleaned out 32' of fill with nitrogen foam. Landed 2-3/8" tubing at 5956' and released the rig on 5-22-85.

I hereby certify that the foregoing is true and correct

SIGNED

BSShaw

TITLE Adm. Supervisor

DATE 6-24-85

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE JUL 02 1985

FARMINGTON RESOURCE AREA

BY Smm

*See Instructions on Reverse Side

NMOCC