

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☒ Recompletion

2. NAME OF OPERATOR
Amoco Production Company

Attention:

Gail M. Jefferson, Rm 1942

3. ADDRESS AND TELEPHONE NO.
P.O. Box 800, Denver, Colorado 80201 (303) 830-6177

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)
At surface 790' FNL 1650' FWL

At top prod. interval reported below

At total depth

RECEIVED
MAY 11 1995
OIL CON. DIV.

5. LEASE DESIGNATION AND SERIAL NO.
NM-03380

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
BLM

7. UNIT AGREEMENT NAME
SOMER-5 FH 245

8. FARM OR LEASE NAME, WELL NO.
WOT Range 1, #62

9. API WELL NO.
3004511729

10. FIELD AND POOL, OR WILDCAT
Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Section 20

Township 27N Range 8W

14. PERMIT NO.

DIST. 3

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

15. DATE SPUDDED 4/25/66 16. DATE T.D. REACHED 5/22/66 17. DATE COMPL. (Ready to prod.) 5/3/95

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6752 GR 19. ELEV. CASINGHEAD 6752

20. TOTAL DEPTH, MD & TVD 7,464' 21. PLUG, BACK T.D., MD & TVD 7,425' 22. IF MULTIPLE COMPL., HOW MANY* 2

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*
Mesaverde 5,112'-5,210'

26. TYPE ELECTRIC AND OTHER LOGS RUN
CBL, CCL, Gamma Ray 500'-5,500'

27. WAS WELL CORED
No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
10-3/4"	32.75#	518'	12-1/4"	250 sx.	None
4-1/2"	11.6 & 10.5#	7445'	7-7/8"	300 sx. 1st stg, 80 sx. 2nd stg, 385 3rd stage	1759 junk
4-1/2"	11.6#	2058'	7-7/8"	None	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
	NONE				2 3/8"	7352'	

31. PERFORATION RECORD (Interval, size and number)

5112-5132'; 5152-5162'; 5168-5176'; 5180-5184'
5188-5192'; 5206-5210'
w/jspf, 0.34 in diam., total 100shots fired.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5112-5208'	636 bbls wtr, 102,570# 16/30 sand, 70 quality foam, 959,275 scf, Max PSI 4,500 PSI, Max Rate 60.0 BPM

33.* PRODUCTION

DATE FIRST PRODUCTION 5/3/95		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) Flowing				WELL STATUS (Producing or shut-in) SHUT IN	
DATE OF TEST 5/3/95	HOURS TESTED 24	CHOKE SIZE 1/2"	PROD'N FOR TEST PERIOD Trace	OIL - BBL 1110 mcf	GAS - MCF 6 bbls	WATER - BBL	GAS-OIL RATIO
FLOW TUBING PRESS NA	CASING PRESSURE 165#	CALCULATED 24-HOUR RATE	OIL - BBL	GAS - MCF	WATER - BBL	OIL GRAVITY - API (CORR.)	
			TEST WITNESSED BY				

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
To be sold

TEST WITNESSED BY

ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS

(Perf frac and reperf after test same interval)

MAY 08 1995

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Gail M. Jefferson

TITLE Sr. Admin. Staff Asst.

FARMINGTON DISTRICT OFFICE

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

WMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof, cored intervals, and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Pictured Cliffs	2780'	3010'	
Mesaverde	4370'	4910'	
Dakota	7168'	7405	Sand Gas

38.

GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH