

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 3249, Englewood, CO 80155
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450'FSL, 910'FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Amended

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

10

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF-079232
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Bolack B
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 29, T27N, R8W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6311' ground

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/24/81 MIRUSU. Set cement retainer @6650'. Squeezed Dakota perms w/ 100sx Class-B. Put 1 bbl of cement on top of retainer.

Set the following cement plugs: 6340-5549 60 sx
4850-2215 200sx
2215-1886 25 sx
1634-1305 25 sx
120-surface 25sx

Unable to pump into bradenhead. RDMOSU

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John Cook TITLE Proj. Prod. Engr. DATE October 8, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

Instructions on Reverse Side
NMCCO

RECEIVED
DEC 27 1984
OIL CON. DIV.
DIST. 3

APPROVED
AS AMENDED

DEC 20 1984

M. MILLENBACH
AREA MANAGER