

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED
BLM

RECEIVED
SEP - 1994
OIL CON. DIV.
DIST. 8

Sundry Notices and Reports on Wells **51 AUG 11 AM 10:34****070 FARMINGTON, NM**

Lease Number
SF-079937

1. **Type of Well**
GAS

6. **If Indian, All. or
Tribe Name**

2. **Name of Operator**
MERIDIAN OIL

7. **Unit Agreement Name**

3. **Address & Phone No. of Operator**
PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. **Well Name & Number**
Turner Hughes #17

9. **API Well No.**
30-045-11815

4. **Location of Well, Footage, Sec., T, R, M**
1450'FNL, 890'FEL, Sec.10, T-27-N, R-9-W, NMPM

10. **Field and Pool**
Blanco MV/Basin DK

11. **County and State**
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**Type of Submission****Type of Action**

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☒ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

7-31-94 MIRU. ND master valve, NU BOP. TOH w/214 jts 2 3/8" tbq. TIH w/5 1/2" scraper, tag fill @ 6666'. TOH. TIH w/5 1/2" RBP & pkr.

8-1-94 Set RBP @ 6460'. TOH. PT RBP to 1000 psi, OK. TIH, release plug @ 6460'. TOH. Reset RPB @ 4340'. PT RBP to 1000 psi, dump one sx sd on top of plug. TOH to 3734'. Isolate csg leak @ 3997-4002'. TOH. TIH w/5 1/2" pkr. set pkr @ 3793'. Pressure up on backside to 700 psi. Pump 200 sx Class "B" neat cmt w/3% water loss (354 cu.ft.). Hesitate sqz. WOC. Release pkr, TOH. TIH to 3750'. WOC.

8-2-94 Tag cmt @ 3866'. Milling.

8-3-94 Drill cmt @ 3933-4002'. PT csg to 750 psi/15 min, OK. TOH. TIH w/retrieving head. Circ sd off top & release BP. TOH. TIH w/4 3/4" WO bit to 4000'. TOH. TIH, tag fill @ 4506'. CO to 4632'.

8-4-94 CO. TIH w/5 1/2" scraper to 4830'. TOH. TIH w/5 1/2" RBP, set @ 4695'. TOH. TIH w/5 1/2" PB pkr, set @ 4634'. PT plug to 1000 psi, OK. Dump two sx of sand. TOH to 4318', set pkr. RU. PT lines to 2000 psi. Pump 20 bbl 2% KCl wtr, 2500 gal 15% HCl. Release pkr, reset pkr @ 4318'. Swabbing.

8-5-94 Release pkr. TOH. Two slip dies sheared off. TIH, fish. TOH. TIH w/retrieving head to 4685'. Blow well. RBP @ 4695'.

8-6-94 Release RBP. Ran 214 jts 2 3/8" 4.6# J-55 10RDEUE tbq set @ 6712. ND BOP. NU master valve. RD. Release rig @ 9:00 p.m.

14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs Date 8/8/94

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

AUG 30 1994

FARMINGTON DISTRICT OFFICE

NMOCD