## STATE OF NEW MEXICO

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Jet.	35 Twp	274 Rge.	9W	County S	anJuan		
NAME OF	TYPE OF	PROD.	METHOD OF PROD. (Flow or Art Lift)	PROD. MEDIUM (Tog. or Cag.)			
etion McSavera	(va:		Flour	The			
otion Dikota	(20)		Flour	To			
	PRI	E-FLOW SHUT-IN		· · · · · · · · · · · · · · · · · · ·	7.00		
Hour, date shullin	Length of tir	Length of time shut-in			Stabilized? (Yes or No)		
Hour, date shut-in	Length of the	5 DAYS	Si press. psig	Stabilized? (Yes or No)			
		FLOW TEST	TNO 1	<u></u>			
ced at thour, dates* [0.6.5.3				Upper or Lowerts Lower			
TIME LAPSED SING		PRESSURE Ion Lower Completion	PROD. ZONE	RE	REMARKS		
-4-93	A	. 8		Opened	aura		
.5.53	0	- 8			leur to		
1-(193	A	. &			Seconds.		
7-7-92	Δ	_ 4		22.10 111	SQL VIS.		
2893	A						
2.0					<del></del>		
ction rate during test							
		Phle	ia Ua	ırs Grav	COR		
1					GOR		
		ACFPD; Tested thr					
Hour, date shut-in	MII	D-TEST SHUT-IN I	PRESSURE DAT		Man on Mah		
len .		cargin of time grights		Stabilized	(Yes or No)		
Hour, date shut-in	Length of tim	ne shut-in	SI press. psig	Stabilized?	(Yes or No)		
e e ek							
	•						
		(Continue on		. 977, 236; 177, 24, 1			

~			FLOW TEST	NO. 2				
Commenced at (hour, da	1(0) 平中		Zone pres	Zone prediging (Upper or Lower):				
TIME	LAPSED TIME	PRESSURE		PROD. ZI	DHE	REMARK	REMARKS	
	SINCE **	Upper Completion	Lewer Completion	TEM		(15/merring		
				1				
					)			
	· · · · · · · · · · · · · · · · · · ·	<del>                                     </del>	<del> </del>	<del>                                     </del>				
	<del></del>							
				<u> </u>				
– Production rate o	during test	_						
Dil: BOPD based on Bbl			Bbls. ir	1	Hours	Grav	GOR	
				(Office C				
Remarks:		<del></del>	<del> </del>		<del></del>	<del></del>	4	
		· · · · · · · · · · · · · · · · · · ·						
1 haarbaifa		· · · · · · · · · · · · · · · · · · ·	:	mplete to	the best of	my knowledge		
		tion herein conțai					<b>T</b>	
Approved	OCT 19	1993	19 (	Operator	Mec	dian Oil	Inc.	
	Oil Conservation			•				
			1	Ву	SUS	AN DOLAN		
n Örsimi	ACCESSON		Title	OPERATIONS ASSISTANT				
By Orafact Agned by CHARLES CHOLSON						1 5 5 5		
Title DEPUTY SIL & GAS INSPECTOR, DIST. #3				Date				

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and dismisally theleafted as prescribed by the order authorizing the multiple completion. Such pesse shall also be commenced on all multiple completions within seven days following decompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall motify the Division in writing of the exact tune the test is to be commenced. Offset operators shall also be so notified.
- 5 The packer leakage test shall commence when hoth zones of the dual completion are shut-in for pressure stabilization. Both zones shall raiman shut-ing until the well-head pressure in each has stabilized, provided however, that they need notifernain shut-in more than zeron days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains state-in. Such test shall be continued for seven days in the case of a gas well and for 24 houseins: the case of arrival well. Note: if, on an initial packer leakage test, a gas well is being flatted to the acmombere due to the lack of a gipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even thangs no loak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is publiced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge is time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fafteen-manuse intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement inamediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable and district the pressure of the conclusion of each flow period.

tronable test dita.

24-hour oil some tests: all pressures, throughout the entire test, shall be continuously measured and becorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a deadweight pethane gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being untern on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon all well as the flowing , temperatures tips somes only) and gravity and GOR (oil zones only).