MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool	Under	rigne to	d	Fo	rmation	D	aleota		_County_		en Ju	Dia .
Initial	X		_Annual			Spec	ial	<u> </u>	Date of	Test	6/23	/60
Company	Appe (<u> </u>	na Cong			Lease		aka "D"	Wel	Ll No	1	1
Unit	L _s	ec	Twp.	#	Rg_Rg	e. 9W	Pur	chaser				
Casing_	W	t. 9.	5 _1.D	. 4.4)90 Se	t at	5768 P	erf6	510	То	734	
Tubing_	2 W	t	-7 I.D	3	995 Se	t at 🎒	10 P	erf. Pin c	ollared_	То		
Gas Pay:	: From_	6520	To_6	/et	_L	Arjo x	G 0.6 9	_GL	606	_Bar.Pr	ess	12
Producin	ng Thru:	Cas	ing		Tu	bing	x	Type We	:11		ngle	·
Date of	Complet	ion:	6/16/	160	Packe	r	Si	ngle-Brade Reservo	enhead-G. oir Temp.	G. or	G.O. I	oual
							ED DATA					
Tested T	C hrough	EPF6	(Ch	oke)		Ĺ	• .		Туре Тар	os		
		F]	Low Dat	a.			Tubin	g Data	Casing I	ata	- -	
No. (Prover)	(Chol	ce) P		Diff.	Temp.	Press	. Temp.		Temp.		Duration of Flow
	Size	Siz	ze	psig	h _w	°F.		°F.		[⊃] F•	ļ	Hr.
SI l.		0.6					20A3		2043 			7 days
2 . 3.								<u> </u>				
4. 5.												
<u> </u>						FLOW CAL	CITATTO	NS	<u> </u>	_l		
No.	Coefficie	ent		Pre		Flow	Temp.	Gravity Factor	Compre			of Flow
	(24-Hou	r) -	$\sqrt{\mathrm{h_{\mathbf{w}}p_{\mathbf{f}}}}$	- 1	psia	F.	t.	$^{ extsf{F}}_{ extsf{g}}$	Fpv	1	@ 15.	025 psia
1. 1.	.307			1	S6	1.000		0.9668	1.0	2		3,858
3.												
4. 5.												
					PRI	ESSURE C	ALCUTAT:	IONS				
	id Hydro					cf/bbl.			fic Gravi			
ravity o c	of Liquid	и нуаго 	(1-	-s		deg.		Pc	fic Gravi	_Pc		1u1a
									γ·····			
No. Pw		$P_{\mathbf{t}}^2$	F _c Q		$(F_cQ)^2$	(F	_{cQ)} ² -e-s)	P _w 2	$P_c^2 - P_w^2$	1	al.	₽ <u>₩</u> ₽ <mark>c</mark>
	(psia)					(1	-e ^{-s})	48.76	No see 2	<u>-</u>	w	P _C
1. 2. 3. 4.												
4.			-							 	İ	
Absolute	Potent:	ial:				MCFPD;	n	9.75				
	Astro 6				. May 1	lunt op						
	d TITLE					NS		L	. M. Stav	ome, Di	st. B	NETA
COMPANY_						REM	ARKS					
						n.em	CAMA					
										c		
											17 1	
										U (1	1960	<i>]</i>
									, J	JL 1 IL CON DIST	. CUN	1./

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_cI 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

STATE OF NEV	y regict)
OIL CONSERVATION		
AZTEC DISTRI	(1 UTHIC	t
NUMBER OF COPIES RECEI	VED	3
£ sf. ic.		
SANTA FE	-1	_
FILE		
U.S.G.S.		
Lair DO OFFICE		_
TRANSPORTER		
PRUMATION OFFICE		
OPEKATOR		1