	5-U9 GS
	1-WD
Nym 9-831a	1-0
(Feb. 1951)	1-F

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
Land Office
Loase No. SF-079114-A
Unit
Campbell Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		XX	SUBSEQUENT REPOR	RT OF WATER SHU	IT-OFF		
NOTICE OF INTENTION TO CHANGE PL		i II	SUBSEQUENT REPOR	RT OF SHOOTING	OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATE	R SHUT-OFF		SUBSEQUENT REPOR	RT OF ALTERING O	CASING.		
NOTICE OF INTENTION TO RE-DRILL O	OR REPAIR WELL		SUBSEQUENT REPOR	T OF RE-DRILLIN	G OR'REPAIR		
NOTICE OF INTENTION TO SHOOT OR		1 1	SUBSEQUENT REPOR	RT OF ABANDONM	ENT		
NOTICE OF INTENTION TO PULL OR A			SUPPLEMENTARY W	ELL HISTORY			
NOTICE OF INTENTION TO ABANDON							
				·			
(INDICAT	E ABOVE BY CHECK MA	RK NAT	JRE OF REPORT, NOTI	CE, OR OTHER DAT	TA)		
					April 13	, J	9 62
/ell No. 6 is locate	ed 790 ft. fro	om_ (12)	$\left\{\begin{array}{l} \mathbf{N} \\ \mathbf{K} \end{array}\right\}$ line and -1	350.ft.from	${f W \choose f W}$ line of	RF	TF/
(½ Sec. and Sec. No.)	(Twp.)	(Rang	ge)	(Meridian)			وأيما
ain Dakota	San	hiao		lies	ate or Territory	APR.	_
sin Dakota (Field)	San (Coun	ty or Sub	division)	*(St	ate or Territory)/; *** X	7 10
					1	CC.	• •
ne elevation of the dexists	xxxx above sea	level 1	is .38333 It. 🤄	SL.	/	$-D/c_{\rm col}$	
ic ciciation or one demande							
ile clovation or one statement	DET	AIIC	OF WORK				
-			OF WORK				engge te ske dide
-				f proposed casing work)	s; indicate mud	ding jobs, c	ment
itate names of and expected depths to	objective sands; show ing points, and a	sizes, we	eights, and lengths o important proposed				
itate names of and expected depths to	objective sands; show ing points, and a	sizes, we	eights, and lengths o important proposed	te depth o	f 6050 fe		
ropose to drill with :	objective sands; show ing points, and a retary tools ion. Casing	to a	eights, and lengths of important proposed in approximation will be	te depth o as follow	f 6050 fe s:	et or	to
itate names of and expected depths to	objective sands; show ing points, and a retary tools ion. Casing	to a	eights, and lengths of important proposed in approximation will be	te depth o as follow	f 6050 fe s:	et or	to
repose to drill with :	objective sands; show ing points, and a rotary tools ion. Casing casing set	to a prog	eights, and lengths of important proposed in approximation will be reximately	te depth o as follow 200 feet w	f 6050 fe s: ith 150 s	et or	to nt.
repose to drill with : est the Dakota format 0 3/4" 32.75# surface 1 10.50# casing set	objective sands; show ing points, and a rotary tools ion. Casing casing set at total dept	to a prog	n approximatem will be reximately a	te depth o as follow 200 feet w ement or c	f 6050 fe s: ith 150 s	et or	to nt.
repose to drill with : est the Dakota format 3/4" 32.75# surface 10.50# casing set	objective sands; show ing points, and a rotary tools ion. Casing casing set at total dept	to a prog	n approximatem will be reximately a	te depth o as follow 200 feet w ement or c	f 6050 fe s: ith 150 s	et or	to nt.
repose to drill with : est the Dakota format 3/4" 32.75# surface 10.50# casing set	objective sands; show ing points, and a rotary tools ion. Casing casing set at total dept	to a prog	n approximatem will be reximately a	te depth o as follow 200 feet w ement or c	f 6050 fe s: ith 150 s	et or	to nt.
ropose to drill with : est the Dakota format 3/4" 32.75# surface " 10.50# casing set allup formation.	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water frac	to a prog	n approximatem will be reximately at the 300 ex co	te depth o as follow 200 feet w mment or c ation.	f 6050 fe s: ith 150 s ement to	et or x ceme cover	to nt. the
repose to drill with : est the Dakota format 3/4" 32.75# surface 10.50# casing set	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water frac	to a prog	n approximatem will be reximately at the 300 ex co	te depth o as follow 200 feet w mment or c ation.	f 6050 fe s: ith 150 s ement to	et or x ceme cover	to nt. the
ropose to drill with : est the Dakota format 3/4" 32.75# surface " 10.50# casing set illup formation. Ill perforate and same	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water frac	to a prog	n approximater will be reximately at the 300 ex continuous forms of the cological states of the cologi	te depth o as follow 200 feet w mment or c ation.	f 6050 fe s: ith 150 s ement to	et or x ceme cover	to nt. the
repose to drill with : est the Dakota format 3/4" 32.75# surface 10.50# casing set 111 perforate and san	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water frac	to a prog	n approximater will be reximately at the 300 ex continuous forms of the cological states of the cologi	te depth o as follow 200 feet w mment or c ation.	f 6050 fe s: ith 150 s ement to	et or x ceme cover	to nt. the
ropose to drill with ropose to drill with ropose to drill with rot the Dakota format 3/4" 32.75# surface 10.50# casing set 11up formation. Ill perforate and san I understand that this plan of work ompany Southwest P	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water fractimust receive approvareduction Commission Commissio	to a prog	n approximate will be reximately at the 300 sx co	te depth o as follow 200 feet w ement or co	f 5050 fe	commence	to nt. the
ropose to drill with : est the Dakota format 3/4" 32.75# surface " 10.50# casing set illup formation. Ill perforate and same	objective sands; show ing points, and a retary tools ion. Casing casing set at total dept d-water fractimust receive approvareduction Commission Commissio	to a prog	n approximate will be reximately at the 300 sx co	te depth o as follow 200 feet w ement or co	f 5050 fe	commence	to nt. the
opose to drill with copose to drill with state Dakota format 3/4" 32.75# surface " 10.50# casing set allup formation. Ill perforate and san Lunderstand that this plan of worksompany Southwest P	objective sands; show ing points, and a retary tools ion. Casing casing set is at total dept d-water frac must receive approvated to Bldg.	to a prog	n approximate will be reximately at the 300 sx co	te depth o as follow 200 feet w ement or co	f 5050 fe	commence	to nt. the
ropose to drill with rost the Dakota format 3/4" 32.75# surface " 10.50# casing set illup formation. Illuperforate and san I understand that this plan of worksompany Southwest P	objective sands; show ing points, and a retary tools ion. Casing casing set is at total dept d-water frac must receive approvated to Bldg.	to a prog	n approximate will be reximately at the 300 sx co	te depth o as follow 200 feet w mment or c ation.	f 5050 fe	commence	to nt. the
repose to drill with rest the Dakota format 3/4" 32.75# surface " 10.50# casing set Illup formation. Ill perforate and san understand that this plan of work ompany Southwest P ddress 207 Petroleum Farmington, Ne	objective sands; show ing points, and a retary tools ion. Casing casing set is at total dept d-water frac must receive approvated to Bldg.	to a prog. apposite wi	eights, and lengths of important proposed in approximate ram will be reximately at the 300 ex contains by the Geological By	te depth o as follow 200 feet w ement or co	f 6050 fe	cover	nt. the

NUMBER OF COPIE	S RECEI	VES				
015	DISTRIBUTION					
SANTA FE		1	T			
FILE						
U. S. G. S.						
LAND OFFICE						
TRANSPORTER	OIL					
IRANSFORTER	GAS		.]			
PRORATION OFFIC	E		Ι			

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

FORM C-128 Revised 5/1/57

TRANSPORTER OIL GAS PROGRATION OFFICE OPERATOR		SEE INSTI	RUCTIONS FO	OR COMP	PLETING TH	IS FORM	ON THE REV	ERSE S	IIDE
			S E	CTIO	<u> </u>				
Operator	DEVIDATOR	13/N:89: - ****	L	.ease					Well No.
SOUTHWEST Unit Letter Se	PRODUCTION ection	Township					F-079114-	<u> </u>	6
C	27	27 NO)RTH	Range	e 2 west	County	TAN MINT		
Actual Footage Loca					- 11201	<u> </u>	SAN JUAN		
790 fe	eet from the	NORTH	line and	1850	fee	t from the	HIST	1	ine
Ground Level Elev.	Producing F	ormation	P	ool			· · · · · · · · · · · · · · · · · · ·		ated Acreage:
5835.0		kota		Ba	sin Dakot				/320 Acres
another. (65-3-). If the answer to que wise? YES	e only owner in to drill into an. 29 (e) NMSA 19 uestion one is _ NO I	the dedicated d to produce fr 35 Comp.) "no," have the f answer is "y	e interests of a	nd to app all the o Consolid	wners been co	production onsolidate	either for hin	nself or	
. If the answer to qu	uestion two is '	'no,'' list all t	the owners and	l their re	spective inte	rests bel	Sw: TIZE	717	
Owner					and Descript	ion	APP.	<u>د د د د د د د د د د د د د د د د د د د </u>	<u> </u>
				\prod			OIL COIV.	~ਪਾ∑ੇ C O∧-	<u></u>
		SECTIO	N B				7	,	IFICATION
		Administration of the state of	 2 7			·	in SECTION plete to the belief. Name Position Assista Company Southwe Date	ON A ai he best	that the information bove is true and comof my knowledge and Jede: Kek, sperintendent roduction Co.
•		to the second day and day for graph of graphs and consider the second of the second day and day and day of the second of the sec					shown on toplotted from surveys mand supervision and correct and belief. Date Surve	the plat m field ade by r n, and t t to the yed Profes	ssional Engineer
330 660 990	1320 1650 198	00 2310 2640	2000	1500	1000 50	× 6	Certificate		Leese 1463 Lincering Compa

INSTRUCTIONS FOR COMPLETION OF FOR & C-128

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of the Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3 of Section A, please use space below.