FARMINGTON OFFICE CEPAtroved. Pudget Bureau No. 42-R359.4.

	m 9-2 April 19			, <u>, , , , , , , , , , , , , , , , , , </u>	 -,
П	A	PF	₹	ROVE	D
X		М	Α	1 7 1962	DEP
	R	iCH.	ΑR	D B. KRAI	HL
	A	TING	D	STRIGT ENGIN	IEER I

(SUBMIT IN TRIPLICATE)

UNITED STATES

ARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

andian Agency							
Allettee							
1-89-IND-57							

		X SUBSEQUENT RE	PORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE P	Į.		PORT OF SHOOTING OR ACIDIZING	OENN
NOTICE OF INTENTION TO TEST WATE	i i	SUBSEQUENT RE	PORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL (SUBSEQUENT RE	PORT OF REDRILLING OR REPAIR	104
NOTICE OF INTENTION TO SHOOT OR		- 1	PORT OF ABANDONMENT	1371 T 1 12
NOTICE OF INTENTION TO PULL OR	ALTER CASING	SUPPLEMENTARY	WELL HISTORY	
NOTICE OF INTENTION TO ABANDON	WELL			CEOTOCICO,
			<u>U. 5</u>	THE TON LET
(INDICAT	TE ABOVE BY CHECK MARK	NATURE OF REPORT, N	OTICE, OR OTHER DATA) [A.A.	1111
	-		May 16	, 1962
		O.D.	(47)	
ell No. <u>26</u> is loc	cated 1980 ft. fro	om $\left \begin{array}{c} \mathbf{N} \\ \mathbf{X} \end{array} \right $ line and .	660 ft. from line	of sec. 3
NW/4 Sec. 3 (4 Sec. and Sec. No.)		• •	NMPM	
		(Range)	(Meridian)	
Table Wesa		n County or Subdivision)	New Mexic (State or Territo	
(Field)	, ,		• • • •	*37
he elevation of the derrick	floor above sea le	vel is 5380 ft.		
·		ILS OF WORK		
State names of and expected depths t	o objective sands; show si	zes, weights, and length other important propo	is of proposed casings; indicate my sed work)	udding jobs, semer
e propose to dril	l this well	with rotary	tools to an es	timated
e propose to dril	l this well the top of t	with rotary he Dakota f	tools to an es	timated oximately
epth of 1450' to '	the top of t D. casing wi	he Dakota f 11 be run a	ormation. Apprint of the control of	oximately surface.
epth of 1450' to 4450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Apprint of the control of	oximately surface.
epth of 1450' to 4450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	'ormation. Approind cemented to : 1/2" casing with	oximately surface. cable
epth of 1450' to 450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	'ormation. Approind cemented to : 1/2" casing with	oximately surface.
epth of 1450' to 450' of 5 1/2" 0. e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Approind comented to a large with operations B	oximately surface. cable Y: Oxox Acmi' RD LESSEE
epth of 1450' to 450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Appro- ind cemented to a L/2" casing with OPERATIONS B ☐ RECO ☐ D. CF	oximately surface. cable Y: Our Acmi RD LESSEE F O. ON FILE
epth of 1450' to 4450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Approind comented to a large with casing with precedured to the coment of t	oximately surface. cable Y: Oxor Acmi RD LESSEE F O. ON FILE F O. ATTACHED
epth of 1450' to 4450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Apprind comented to a large with comented to a large with constant with constant and constant and constant and covers and	oximately surface. cable Y: Oper Pami RD LESSEE F O. ON FILE F C. ATTACHED GE. DISPLACE TO THE TACHED
epth of 1450' to 450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un	he Dakota f 11 be run a der the 5 1	ormation. Apprind comented to a large with comented to a large with constant with constant and constant and constant and covers and	oximately surface. cable Y: Oxor Acmi RD LESSEE F O. ON FILE F O. ATTACHED
epth of 1450' to 450' to 450' of 5 1/2" 0. e will then drill ools and complete	the top of t D. casing wi out from un the well op	he Dakota fill be run a der the 5 leen hole.	Cormation. Apprind comented to solve the coment of the coverable c	oximately surface. cable Y: Opene Dom! RD LESSEE F O. ON FILE F C. ATTACHED GE: INDIA LO ATTACHED LO CON FILE
epth of 1450' to 450' of 5 1/2" 0.0 e will then drill	the top of t D. casing wi out from un the well op	he Dakota fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
epth of 1450' to the state of t	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Opene Dom! RD LESSEE F O. ON FILE F C. ATTACHED GE: INDIA LO ATTACHED LO CON FILE
epth of 1450' to 1450' to 1450' of 5 1/2" 0. e will then drill ools and complete	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
Company Centinent	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
epth of 1450' to 1450' to 1450' of 5 1/2" 0. e will then drill ools and complete	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
epth of 1450' to 450' of 5 1/2" 0. 450' of 5 1/2" 0. e will then drill ools and complete Tunderstand that this plan of wor Company Centinent Address Box 3312	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
epth of 1450' to 450' of 5 1/2" 0. e will then drill ools and complete I understand that this plan of wor	the top of t D. casing wi out from un the well op	he Dakote fill be run a der the 5 leen hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Open Demi RD LESSEE F O. ON FILE F C. ATTACHED BE DIVIDA BO ON FILE FOR THE BOOK FILE FOR THE BOOK FILE FOR THE BOOK FILE FILE BOOK FILE
epth of 1450' to 450' of 5 1/2" 0. 450' of 5 1/2" 0. e will then drill ools and complete Tunderstand that this plan of wor Company Centinent Address Box 3312	the top of t D. casing wi out from un the well op	he Dakote in the Salamen hole. It is not been hole.	ormation. Apprind comented to a line comented to a line with operations because of the control o	oximately surface. cable Y: Own Flow RD LESSEE F O. ON FILE F C. ATTACHED DO ATTACHED DO ON FILE TYPE HATTACHED ATTACHED TYPE HATTACHED TYPE