

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 H1424.
6. LEASE DESIGNATION AND SERIAL NO.
SF-077123

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Tenneco Oil Company		8. FARM OR LEASE NAME Warren Com.	
3. ADDRESS OF OPERATOR P. O. Box 1714, Durango, Colorado		9. WELL NO. #2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1990 FNL, 1585 FEL, Unit		10. FIELD AND POOL, OR WILDCAT Basin Dakota	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14, T-28-N, R-9-W	
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 6106 Gr.		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☒
SHOOTING OR ACIDIZING ☒
(Other) ☐REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rigged up completion rig 5/23/67. CO to 7020 PBD. Perf 7004-07, 6978-91, 6963-73, 6952-53 w/1 HPF. Acidized w/250 gals 7-1/2% HCL. Frac w/60,000# 20-40 sand and 3500# 12-20 glass beads. Avg Inj rate 49 BPM @ 3600 psi. Perf w/1/ft. 6925, 6922, 6904, 6902, 6891, 6846-60, 6814-18. Frac w/60,000# 20-40 sd and 3500# 12-20 glass beads. Avg rate 66 BPM @ 3300 psi. CO to 7020. Ran 221 jts 2-3/8" 4.7# J-55 tbg set at 7005. Rel rig 5/24. WO Test.



RECEIVED

MAY 29 1967

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. K. Wagner

TITLE

DATE May 26, 1967

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

5 USGS

1 Cont.

*See Instructions on Reverse Side