

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
790'FSL, 1500'FEL Sec.35, T-27-N, R-9-W, NMPM

5. Lease Number
SF-078135

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
Huerfanito Unit

8. Well Name & Number
Huerfanito U #98M

9. API Well No.
30-045-28946

10. Field and Pool
Blanco MV/Basin Dk

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

05-12-93 TD 232'. Spud @ 5:00 pm 5-12-93. Ran 5 jts 8 5/8", 24.0#, K-55 csg, 217' set @ 230'. Cmt w/210 sx Class "B" w/3% calcium chloride and 0.25#/sx flocele (248 cu.ft.). Circ 12 bbl to surface.

05-23-93 TD 6768'. Ran 158 jts. 4 1/2", 11.6#, K-55 casing, 6755' set @ 6768'. Float collar set @ 6723'. Stage tool @ 4499' and 1581'. Cemented first stage with 467 sks. Class "G" 65/35 Pozmix, 6% gel, 1/4#/sx cello-seal and 2% calcium chloride, (827 cu.ft.), tailed w/100 sx Class "G" w/2% calcium chloride (115 cu.ft.). Circ 25 bbl to surface. Cemented 2nd stage with 610 sks. Class "B" 65/35 Pozmix, 6% gel, 2% calcium chloride, and 1/4#/sx cello-seal (1080 cu.ft.), tailed w/100 sx Class "B" w/2% calcium chloride (115 cu.ft.). Circ 22 bbl to surface. Cemented 3rd stage w/340 sx Class "B" 65/35 Poz w/6% gel, 2% calcium chloride and 0.25#/sx celloflake (602 cu.ft.), tail w/100 sx Class "B" w/2% calcium chloride (115 cu.ft.). Circ 24 bbl cmt to surface. WOC 18 hours.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 5/24/93

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any: _____

Date
JUN 01 1993

NMOCD

FARMINGTON DISTRICT OFFICE

BY [Signature]