

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.  
*NM-012202*  
*NM-40635*

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

1. Type of Well  
☐ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
**AMOCO PRODUCTION COMPANY**  
Attention: **BOBBE BREN-CARLEY**

3. Address and Telephone No.  
**P.O. Box 800, Denver, Colorado 80201**  
**(303) 830-4542**

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
*1090' FNL & 1805' FEL* Sec. 33 T 28N R 8W UNIT B

8. Well Name and No.  
**BOLACK B LS #7**

9. API Well No.  
**3004520446**

10. Field and Pool, or Exploratory Area  
**BLANCO-PC**

11. County or Parish, State  
**SAN JUAN NEW MEXICO**

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☒ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**AMOCO PRODUCTION CO. REQUESTS APPROVAL TO IMPLEMENT THE ATTACHED PROCEDURES FOR SLIM HOLE CASING REPAIR OF THE SUBJECT LOCATION.**

**RECEIVED**  
DEC - 6 1993  
OIL CON. DIV.  
DIST 3

DEC 13 1993  
DISTRICT MANAGER

14. I hereby certify that the foregoing is true and correct

Signed *Bobbe Bren-Carley* **BOBBE BREN-CARLEY** Title **SR. BUSINESS ANALYST** Date **11-19-1993**

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date **DEC 03 1993**

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false statement or representation as to any matter within its jurisdiction.

**DISTRICT MANAGER**

\* See Instructions on Reverse Side

**Bolack B LS #7**  
**33B-28N-8W**  
**SLIM HOLE CASING REPAIR**

1. Dig flow back pit and fence.
2. Install and/or test anchors.
3. RIH with wireline gauge to check for casing integrity, fluid level and PBTD.
4. Check and record casing and bradenhead pressures.
5. Drop sufficient sand to cover PC perfs (2099'-2170'). Top with bentonite plug.
6. Load hole with 2% KCl water and pressure test casing with pump truck. If casing does not pressure test, TIH with wireline plug and locate hole(s). TOH with wireline plug.
7. Add dye to water and attempt circulation through hole(s) to determine cement volumes needed. (Depending on circulation and injection rate, perf holes maybe necessary. If so, shoot 1 ft at 2 JSPF.)
8. Rig up Halliburton Services.
9. Mix up cement and attempt to circulate to surface until returns are seen at the surface through the Bradenhead. Displace cement with 2% KCl water to within 50-100' of hole(s)/perfs.
10. WOC 18 hours.
11. MIRUSU. NDWH. NUBOP.
12. TIH with drill pipe and collars and tag cement. Pressure test casing to 300#. Drill out cement.
13. Pressure test casing with 2% KCl water to 300#. If pressure does not hold, repeat steps 8-13.
14. If the casing integrity is sufficient, continue to TIH and circulate out KCl water with Nitrogen. Circulate out plug and sand to PBTD to kick well off. TOH with drill pipe and collars.
15. RDMOSU. NDBOP. NUWH.

16. Record casing and Bradenhead pressures.

**IF ANY PROBLEMS ARE ENCOUNTERED, PLEASE CONTACT**

**LARA KWARTIN:**

**W-303-830-5708**

**H-303-830-4130**

BOLACK B LS 007  
LOCATION - B33-- 28N- 8W  
SINGLE PC  
ORIG.COMPLETION - 4/69  
LAST FILE UPDATE - 10/93 BY CSW

