OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator SOUTHLAND ROYALTY COMPANY				Lease _	HILLSIDE	Well No. #1		
ocation f Well: Uni	t J 9	Sec. <u>09</u>	_ Twp27	, Rge	11	Co	unty SAN JUAN	
NAME OF RESERVOIR OR POOL			TYPE OF I	PROD.	METHOD OF PRO	DO. PROD. MEDIUM		
Completion GALLUP			GAS		FLOW	TUBING		
Completion DAKOTA			GAS		FLOW	TUBING		
			PRE-FL	OW SHUT-IN P	RESSURE DA	TA		
Upper completion 5/5/90 Length of time shut-in Length of time shut-in 3 DAYS				SI press. psig 367		Stabilized? (Yes or No)		
Lower	date shut-in /5/90		Length of time sh 3 DAYS	Length of time shut-in 3 DAYS			Stabilized? (Yes or No)	
				FLOW TEST	NO. 1			
mmenced at (ho	ur, date)*	5/8/90	,		Zone producin	(Upper or Lower):	LOWER	
TIME (hour, date)		SINCE*	PRES Upper Completion	SURE Lower Completion	PROD. ZONE TEMP.		REMARKS	
5/6/90	1	DAY	367	370		вотн Z	ONES SHUT-IN	
5/7/90	2	DAYS	367	375		вотн Z	ONES SHUT-IN	
5/8/90	3	DAYS	367	378		вотн Z	ONES SHUT-IN	
5/9/90	1	DAY	367	317		LOWER	ZONE FLOWING	
5/10/90		DAYS	367	320		LOWER	ZONE FLOWING	
oduction ra	e during t	est				-····. ¹		
l:	·	ВОРІ	D based on	Bbls. in	Но	urs G	rav GOR	
s:				D: Tested thru (
MID-TEST SHUT-IN								
Upper Length of time shut-in projection				il press. psig		Stabilized? (Yes or No)		
Lower Mour, date shut-in Length of time shut-in mpletion]	il press, psig		Stabilized? (Yes or No)		
				DEBE	VE	i		

JUL 9 1990

OIL CON. DIV

(Continue on reconseguie)

FLOW TEST NO. 2

Commenced at (hour, date) ** Zone producing (Upper or Lower):								
TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE				
	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS			
								
								
			•					
				-				
Production rate	during test							
Oil:	BOP	D based on	Bbls. in	Hours.	Grav GOR			
~								
Jas:		MCF	PD: Tested thru	(Orifice or Meter	·):			
Remarks:								
					<i>,</i>			
hereby certify	that the information	on herein contain	ed is true and cor	nplete to the bes	et of my knowledge.			
_	JUL 🤊 19	9()						
Approved			_ 19 O	perator <u>SOU</u>	THLAND ROYALTY COMPANY			
New Mexico	Oil Conservation D)ivision	77					
_			ָמ	y 	C.I. CHANDLER			
By0	riginal Signed by CHA	RLES GHOLSON	η-;	itle	PRODUCTION ASST.			
				Date JUL 0 6 1990				
Title0	EPUTY OIL & GAS IN	SPECTOR, DIST. #3	D					

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall noury the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so nouried.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more so than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in according dance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be elected at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gadge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-91-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).