

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Southland Royalty Company  
3. ADDRESS OF OPERATOR  
P.O. Drawer 570, Farmington, NM 87499  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1850' FNL & 850' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
DEC 14 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-25-82 Pull out of hole with 215 joints 1-1/2" tubing.  
11-26-82 Trip in with 3-7/8" mill & casing scraper to 6990'. Set drillable bridge plug at 6797' above Dakota perms.  
10-27-82 Run full bore packer and pressure test casing from 4851' to 6990' at 1100 psi. Drill out bridge plug and clean out to 6995'.  
10-28-82 Set packer at 6866'. Acidize lower Dakota with 1500 gallons 15% HCL with 900 SCF N2 per barrel at 5-1/2 BPM at 2800 psi. Flow to pit to clean up.  
10-29-82 Set retrievable bridge plug at 6905' and packer at 6811'. Acidize upper Dakota. Acidize with 1500 gallons 15% HCL acid with 900 SCF N2/barrel. Pull out of hole with bridge plug and packer.  
10-30-82 Landed 215 joints 1-1/2" tubing at 6917'. Shut in for pressure build up.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineer DATE December 13, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

DEC 14 1982

\*See Instructions on Reverse Side

NMOCC