ce for Federal or State office use

/s/Charlie Beecham

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004 0135
Expires: March 31, 1993

2000

BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS SF - 078499 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6 If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT - " for such proposals 7. 11 Unit or CA, Agreement Designation MAR 2000 X Gas RECEIVED iame of Operator Tapp LS OIL GON, DIV AMOCO PRODUCTION COMPANY Mary Corl DIST. 3 30-045-20920 3 Address and Telephone No 281-366-4491 P.O. BOX 3092 HOUSTON, TX 77253 oi, or Expioratory Area Pictured Cliffs 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 22 T 28N R **UNIT B** Sec. 800' FNL 1840' FWL SAN JUAN **NEW MEXICO** CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Change of Plans \bowtie Notice of Intent New Construction Non-Routine Fracturing Subsequent Report Casing Repair Water Shut-Off BLM LTR 9/10/1999 ed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give Amoco Production Company request permission to plug and abandon the subject well as follows: 1. Notify regulatory agencies (BLM, NMOCD, FIMO) 24 hours in advance of plugging activity. Contact BLM and indicate well is allotted (FIMO regulations effective April 1, 1997). 2. Rigless operation. Blow down well. 3. Bullhead Class B neat cement down casing to abandon PC. Leave cement top at 1,791' to cover Ojo Alamo. Wait on cement 3 hours. Perforate squeeze holes at 550'. Pump down casing and circulate cement to surface. Use 65:35 POZ and tail in with 100 sacks Class B neat cement leaving casing full of cement. 4. Cut off casing and wellhead. Install PXA marker according to BLM or state requirements. 5. Contact FMC and ship surface equipment to yard or other location per instructions. 6. Provide workorder to Buddy Shaw for reclamation. 7. Rehabilitate location according to BLM or State requirements. 02-10-2000 Sr. Business Analyst

* See Instructions on Reverse Side

MACCO