

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 080112

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Riddle F

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Blanco P. C. Ext.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 8, T-28-N, R-8-W
NPMP

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5914'GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-15-72

T. D. 2465'. Ran 85 joints 2 7/8", 6.4#, J-55 production casing, 2454' set at 2465'. Baffle set at 2454'. Cemented with 335 cu. ft. cement. WOC 18 hours. Top of cement at 1320'.

8-29-72

PBTD 2454'. Perf'd 2346-66' with 36 shots per zone. Frac'd with 27,000# 10/20 sand and 27,470 gallons treated water. No ball drops. Flushed with 600 gallons.

RECEIVED

AUG 31 1972

U. S. GEOLOGICAL SURVEY

RECEIVED

SEP 5 1972

OIL CON. COM.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Petroleum Engineer

DATE

August 31, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side