Form 9-331 (May 1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

SUBMIT IN TRIPLICATE\*

LEAS	æ	U	£.;	-11	ίN	١,	$100  \mathrm{N}$	٨

	Forn Budg	i approv ∽t Bure	ed. au N	o. <b>4</b>	2 -R	1424
LEA	SE DESI	GNATION	AND	SER	IAL	No/
SF	0801	01				

C. IT INDIAN, ALLOTTEE OR TRIBE NAME

VACINID	NOTICES	AND	REPORTS	ON	WELLS
SUNDKT	NOTICE2	MINU	REPORTS	ON	AACEED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals.)

GEOLOGICAL SURVEY

7 UNIT AGREEMENT NAME

S. FARM OR LEASE NAME

Riddle G

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Blanco P. C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 7, 28-N, 8-W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

SUBSEQUENT EEPORT OF:

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

New Mexico

1540' S, 1500' E

OTHER

El Paso Natural Gas Company

MELL , MELL

ADDRESS OF OPERATOR

FRACTURE TREAT

(Other)

SHOOT OR ACIDIZE REPAIR WELL

NAME OF OPERATOR

14. PERMIT NO.

16.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)
At surface

5733' GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON\* CHANGE PLANS

WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING

REPAIRING WELL ALTERING CASING

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

T. D. 2259'. Ran 75 joints 2 7/8", 6.4#, KS production casing, 2248' set at 2259'. Baffle set at 2248'. Cemented with 483 cu. ft. cement. 12-29-72 W. O. C. 18 hours. Top of cement at 930'.

PBTD 2248'. Tested casing, held 4000#. Perfed 2160-2170,2180-2190, 4-16-73 2210-2220' w/30 SPZ. Fraced w/30,000# 10/20 sand and 30,800 gallon Dropped two sets of 30 balls each. Flush w/550 treated water. gallons water.



APR 2 3 1973

U. S. GEOLOGICAL SURVEY

3. I hereby certify that the foregoing is true and correct		
SIGNED #10 / LOOS	THILE Petroleum Engineer	DATE April 18, 1973
(This space for Federal or State office use)		
	•	
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		