

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-077382

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Petroleum Corporation of Texas

3. ADDRESS OF OPERATOR

Box 911, Breckenridge, Texas 76024

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1840' FSL & 1050' FWL Unit Letter L, Sec. 3,
T27N, R10W, San Juan County, New Mexico

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Kutz-Government

9. WELL NO.

7-Y

10. FIELD AND POOL, OR WILDCAT

Fulcher Kutz (PC)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, 27N, 10W

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

6085' GR

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Drilling ☒

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

4-10-73 Move in rig. Spud 7:30 p.m. Drill to 108'. Deviation 3/4 degrees.
Ran 3 jts. 8-5/8" used casing, set @ 107'. Cemented w/90 sx.
cement. Cement circulated. Plug down 2:15 a.m. 4-11-73.

4-11-73 W.O.C. 12 hrs. Started drilling.

4-12-73 Drilling @ 1155' w/bit #4, clear water. Deviation 3/4 degree
@ 1111'.

4-13-73 Mudded up @1900' and drilled to TD 2188. Deviation at 2188
3/4 degree. Made two short trips and pulled out of hole. Ran
Schlumberger. Top of Pictured Cliffs is 1996', bottom is
2074'. Ran 58 jts. 4 1/2" used casing to 2183'. Cemented w/250
sx. Class C, 10% gel and 125 sx. Class C w/5# salt per sack
and .5 of 1% D-31. Displaced w/200 gallons 7 1/2% acetic acid
and sugar water. Plug down @ 8:40 p.m. and rig released.

18. I hereby certify that the above is true and correct

SIGNED

Mary D. Taylor

OIL CON. COM.
DIST. 3

Production Clerk

DATE 4-19-73

(This space for Federal or State)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
DATE
APR 23 1973

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

*See Instructions on Reverse Side