

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

box 4289, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1050'S, 1620'W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐

RECEIVED
JUL 26 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

RECEIVED
JUL 28 1983

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 7-18-83 MOL & RU. Pulled tubing and packer. Set sand plug. Tagged sand plug at 2800'. Ran Baker Model C packer to isolate casing failure. Could not pressure test sand plug.
- 7-19-83 Trip out w/packer and drill pipe and replaced packing element. Trip in hole. Tested sand plug to 2000 psi. Held O. K. Isolated holes between 257' and 641'. Squeezed w/236 cu. ft. cement. After good cement returned to surface shut in bradenhead. Final squeeze pressure 500 psi. W.O.C. 18 hours.
- 7-20-83 Tagged cement at 140'. Drilled cement to 620'. Pressure tested to 750 psi. Bled off to 500 psi and stabilized. Trip in w/casing scraper. Tripped out of hole.
- 7-21-83 Cleaned out to total depth w/gas. Ran 92 joints 1 1/4", 2.33# tubing (2974') set at 2983'. Baker Model C packer set at 2850'. Loaded annulus w/corrosion inhibitor. Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Brisco TITLE Drilling Clerk DATE July 26, 1983

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 27 1983

*See Instructions on Reverse Side

NMOCC

FARMINGTON
BY RB