

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 077384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Huerfano Unit

8. FARM OR LEASE NAME

Huerfano Unit Com

9. WELL NO.

118

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T-27-N, R-10-W
NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1.

OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1650'S, 1650'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5981'GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-21-73 TD 6344'. Ran 202 joints 4 1/2", 10.5#, K-55 production casing, 6331' set at 6344'. Float collar set at 6326'. Stage tool set at 4349' and 1916'. Cemented first stage with 351 cu. ft. cement, second stage with 312 cu. ft. cement, third stage with 441 cu. ft. cement. WOC 18 hours. Top of cement at 775'.

1-13-73 PBTD 6326'. Tested casing to 4000#-OK. Perf'd 6310', 6264', 6262', 6210', 6150' and 6124' with one shot per foot. Frac'd with 54,000# 40/60 sand and 57,120 gallons treated water. No balls dropped. Flushed with 4200 gallons water.



JAN 16 1974

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Clerk

DATE

January 16, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: