

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42 R1421.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

SF 078499-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hardie E

9. WELL NO.

2A

10. FIELD AND POOL OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR B.K. AND
SURVEY OR AREA

Sec. 9, T-28-N, R-8-W
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6326' GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☒
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

09-19-76 T.D. 3150'. Ran 77 joints 7", 20#, KS intermediate casing, 3139' set at 3150'. Cemented with 370 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 1600'.

09-22-76 T.D. 5441'. Ran 77 joints 4 1/2", 10.5#, K-55 casing liner, 2440' set 3001-5441'. Float collar set at 5424'. Cemented with 425 cu. ft. cement. W.O.C. 18 hours.

10-21-76 P.B.T.D. 5424'. Tested casing to 3500#, O.K. Perfed 4376', 4457', 4476', 4482', 4488', 4494', 4505', 4509', 4523', 4532', 4548', 4555', 4717', 4750', 4777', 4794', 4875', 4887', 4978', 4991' with 1 shot per zone. Fraced with 65,000#--20/40 sand and 129,948 gallons water. No ball sets dropped. Flushed with 6510 gallons water. Perfed 5046', 5052', 5058', 5064', 5071', 5077', 5083', 5089', 5104', 5117', 5135', 5166', 5177', 5202', 5233', 5247', 5256', 5299', 5317', 5328', 5347', 5381', 5400' with 1 shot per zone. Fraced with 65,000#--20/40 sand and 129,948 gallons water. No ball sets dropped. Flushed with 6346 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. P. Dues

TITLE

Drilling Clerk

(This space for Federal or State office use)

DATE

10-26-76

OCT 26 1976

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

U. S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side

RECEIVED