

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE*
(Other Instructions on Re-
verse side)

Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078499-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hardie E

9. WELL NO.

2A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA
Sec. 9, T-28-N, R-8-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6326' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

09-19-76 T.D. 3150'. Ran 77 joints 7", 20#, KS intermediate casing, 3139' set at 3150'. Cemented with 370 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1600'.

09-23-76 T.D. 5441'. Ran 77 joints 4 1/2", 10.5#, K-55 casing liner, 2440' set 3001-5441'. Float collar set at 5424'. Cemented with 425 cu. ft. cement. WOC 18 hours.

10-21-76 PBTD. 5424'. Tested casing to 3500#, O.K. Perfed 4376', 4457', 4476', 4482', 4488', 4494', 4505', 4509', 4523', 4532', 4548', 4555', 4717', 4750', 4777', 4794', 4875', 4887', 4978', 4991' with 1 shot per zone. Fraced with 65,000#-20/40 sand and *64,974 gallons water. No ball sets dropped. Flushed with 6510 gallons water. Perfed 5046', 5052', 5058', 5064', 5071', 5077', 5083', 5089', 5104', 5117', 5135', 5166', 5177', 5202', 5233', 5247', 5256', 5299', 5317', 5328', 5347', 5381', 5400' with 1 shot per zone. Fraced with 65,000#-20/40 sand and *64,974 gallons water. No ball sets dropped. Flushed with 6346 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Brice

TITLE Drilling Clerk

DATE November 8, 1976

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side