

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R142a.

5. LEASE DESIGNATION AND SERIAL NO.

USNM-8409

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Driskell Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 8 - 27N - 13W

12. COUNTY OR PARISH 18. STATE

San Juan

New Mexico

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Kirby Exploration Company

3. ADDRESS OF OPERATOR  
P.O. Box 1745, Houston, Texas 77001

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

920' FNL & 1150' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5955 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drill 6 3/4" hole to 1548 feet. Run FDC/CNL with GR-Caliper and IEL logs from total depth to surface casing. Logs indicated non-commercial gas deposit. Log tops Kirtland 110 feet, Fruitland 964 feet, and Pictured Cliffs 1309 feet.

Abandonment instructions were received from P. T. McGraph via telephone on 5-22-77.

Ran 2 7/8" drill pipe to 1547 and spot 80 sacks class "B" cement. Plug from total depth to 1200 feet. Pull drill pipe to 210 feet and spot 40 sacks class "B" cement plug back to surface casing, set at 50 feet.

A gel-chem mud, wt. 9.4# per gallon, was left between plugs. Plug complete 0130 hours 5-23-77.

The 8 5/8" casing was cut off below ground level and a one sack class "B" cement plug was placed at the cut off.

The area was cleaned and pits fenced. The pits will be filled when dry and area returned to U.S.G.S. specifications.

18. I hereby certify that the foregoing is true and correct

SIGNED

*John Alexander*  
John Alexander

TITLE

Agent

DATE

5-24-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

