

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42 R1424

LEASE DESIGNATION AND SERIAL NO.

USNM-8409

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Kirby Exploration Company

3. ADDRESS OF OPERATOR
P.O. Box 1745, Houston, Texas 77001

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

920' FNL & 1150' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
5955 GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Driskell Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 8 - 27N - 13W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 6 3/4" hole to 1548 feet. Run FDC/CNL with GR-Caliper and IEL logs from total depth to surface casing. Logs indicated non-commercial gas deposit. Log tops Kirtland 110 feet, Fruitland 964 feet, and Pictured Cliffs 1309 feet.

Abandonment instructions were received from P. T. McGraph via telephone on 5-22-77.

Ran 2 7/8" drill pipe to 1547 and spot 80 sacks class "B" cement. Plug from total depth to 1200 feet. Pull drill pipe to 210 feet and spot 40 sacks class "B" cement plug back to surface casing, set at 50 feet.

A gel-chem mud, wt. 9.4# per gallon, was left between plugs. Plug complete 0130 hours 5-23-77.

The 8 5/8" casing was cut off below ground level and a one sack class "B" cement plug was placed at the cut off.

The area was cleaned and pits fenced. The pits will be filled when dry and area returned to U.S.G.S. specifications.

18. I hereby certify that the foregoing is true and correct

SIGNED

John Alexander

TITLE

Agent

APPROVED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JUN 29 1978

P. T. McGRATH

DISTRICT ENGINEER

*See Instructions on Reverse Side

MAY 25 1977
DATE 5-24-77

U.S. GEOLOGICAL SURVEY

DATE

