Form Approved

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS TO MAKE THE FORM TO BE POPOSSES TO SHARE TO BE GROWN TO	Dec. 1973	Budget Bureau No. 42-R1424
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS Con not use this form for proposals to dill prit to deepen or plug back to a different serverori. Use from 9-331-0 for supproposals, but the form for proposals to dill prit to deepen or plug back to a different serverori. Use from 9-331-0 for supproposals, but the form for proposals to dill prit to deepen or plug back to a different serverori. Use from 9-331-0 for supproposals, but the ground of the g	UNITED STATES	1 2 1
SUNDRY NOTICES AND REPORTS ON WELLS Of not use this form for proposels to drill or to deepen or plug back to a different service. Use form 3-31-2 for such proposals, deepen or plug back to a different well of the form 3-31-2 for such proposals, deepen or plug back to a different service. Use form 3-31-2 for such proposals, deepen or plug back to a different service. Use form 3-31-2 for such proposals, deepen or plug back to a different service. The form 3-31-2 for such proposals, deepen or plug back to a different service. The service is a such proposals to drill or to deepen or plug back to a different service. The service is a such proposal to the service is a such proposal to the service. The service is a such proposal to the service is a such proposal to the service. The service is a such proposal to the service is a such proposal to the service. The service is a such proposal to the service is a		
Continues this form for proposable to differ the deepen or plug back to a different reservoir. Use Form 9-331-C for such proposable. 1. oil	GEOLOGICAL SURVEY	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
1. oil gas with the complete gas with the gas with the gas gas with the gas gas with the gas		
Well No. 2. NAME OF OPERATOR Jerome P. McHugh 3. ADDRESS OF OPERATOR BOX 234, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) 790' FSL - 1710' FEL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE WILL OR ALTER CASING WILL COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Plan to plug and abandon well in the following manner: 1. Spot cement plug from 150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Chins space for Federal or State office use) (This space for Federal or State office use)	reservoir. Use Form 9-331-C for such proposals.)	
Jerome P. McHugh 3. Address of operator Box 234, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 790' FSL - 1710' FEL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: RECTURE TREAT HOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING WILLFILE COMPLETE HANGE ZONES BARADON* 2X Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct SIGNED (This space for Federal or State office use)	1 9*- 1	9. WELL NO.
3. ADDRESS OF OPERATOR BOX 234, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 790' FSL - 1710' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF SHOOT OR ACIDIZE SHOOT OR ACIDIZE CHECK CAPROPERS OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. Thereby certify the the foregoing is true and correct Thomas A. Dugan (This space for Federal or State office use)		393 33
AREA Delow) AT SURFACE: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL		
Section 25-T27N R13W Country or PARISH 13, STATE San Juan 14 API NO. Subsception 25-T27N R13W Country or PARISH 13, STATE San Juan 14 API NO. Subsception 25-T27N R13W Country or PARISH 13, STATE San Juan 14 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Country or PARISH 13, STATE San Juan 18 API NO. Section 25-T27N R13W Section 25-T27N	Box 234, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OF
AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. REQUEST FOR APPROVAL TO: 18. SUBSEQUENT REPORT OF: 19. SUBSEQUENT	· · · · · · · · · · · · · · · · · · ·	
AT TOP PROD. INTERNAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD 5953' GR 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct sounds. Thomas A. Dugan TITLE Agent DATE 5-23-79 (This space for Federal or State office use)	' /9U F3I = 1/1U FF!	
14. API NO. 15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD 5953' GR 15. ELEVATIONS (SHOW DF, KDB, AND WD 5953' GR 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 17. RECUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 18. CHARLE CASING		
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 125. ELEVATIONS (SHOW DF, KDB, AND WD 5953' GR 126. GRACTURE TREAT 127. SUBSEQUENT REPORT OF: 128. SUBSEQUENT REPORT OF: 129. SUBSEQUENT REPORT OF: 129. SUBSEQUENT REPORT OF: 129. SUBSEQUENT REPORT OF: 139. SUBSEQUENT REPORT OF: 149. SUBSEQUENT REPORT OF: 159. SUBSEQUENT REPORT OF: 169. SUBSEQUENT REPORT OF: 169. SUBSEQUENT REPORT OF: 179. SUBSEQUENT REPORT OF: 189. SUBSEQUENT REPORT OF: 199. SUBSEQUENT REPORT OF: 19		14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: STACTURE TREAT SHOOT OR ACIDIZE CRACTURE TREAT SHOOT OR ACIDIZE CRACTURE TREAT SHOOT OR ACIDIZE CREPAIR WELL CROMPLETE CHANGE ZONES BABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type Set Only College Structure of the properties of the pr		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES BANDON* (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct in the policy of the properties of t		15. ELEVATIONS (SHOW DF, KDB, AND WD)
RACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct in the policy of the policy o		3 / 8 · 4 /
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING		
PULL OR ALTER CASING Change on Form 9-330.) MULTIPLE COMPLETE COMPLETE CONES CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Thomas A. Dugan TITLE Agent DATE 5-23-79 (This space for Federal or State office use)	SHOOT OR ACIDIZE	
MULTIPLE COMPLETE CHANGE ZONES (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct signed — J. H. Manualla. Title Agent DATE 5-23-79 (This space for Federal or State office use)	REPAIR WELL	(NOTE: Report results of multiple completion or zone
CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Thomas A. Dugan (This space for Federal or State office use)		change on Form 9-330.)
(other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type Set © Ft 18. I hereby certify that the foregoing is true and correct SIGNED — J. H. Manual Title Agent DATE 5-23-79 (This space for Federal or State office use)	CHANGE ZONES	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Thomas A. Dugan TITLE Agent DATE 5-23-79 (This space for Federal or State office use)	1,	
measured and true vertical depths for all markers and zones pertinent to this work.)* Plan to plug and abandon well in the following manner: 1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu, and Type Set Signed Thomas A. Dugan (This space for Federal or State office use)		
1. Spot cement plug from 1150-1050' 2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED THE Agent DATE 5-23-79 (This space for Federal or State office use)	including estimated date of starting any proposed work. If well is di	rectionally drilled give subsurface locations and
2. Spot cement plug from 960-840' 3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Thomas A. Dugan (This space for Federal or State office use)	Plan to plug and abandon well in the following	ng manner:
3. Spot plug from surface to 200' 4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Thomas A. Dugan (This space for Federal or State office use)	1. Spot cement plug from 1150-1050'	
4. Cut off csg 4' below ground level 5. Clean location Subsurface Safety Valve: Manu. and Type Set © Ft 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Agent DATE 5-23-79 (This space for Federal or State office use)	2. Spot cement plug from 960-840'	
5. Clean location Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED	3. Spot plug from surface to 200'	100000000
Subsurface Safety Valve: Manu. and Type Set © Ft 18. I hereby certify that the foregoing is true and correct SIGNED	4. Cut off csg 4' below ground level	A MAN CONTROL
18. I hereby certify that the foregoing is true and correct SIGNED	5. Clean location	DIST
Thomas A. Dugan (This space for Federal or State office use)	Subsurface Safety Valve: Manu. and Type	Set @Ft.
(This space for Federal or State office use)	18. I hereby certify that the foregoing is true and correct	
	SIGNED Thomas A. Dugan TITLE Agent	DATE 5-23-79
APPROVED BY		Ce use)
THILE DATE	APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE

*See Instructions on Reverse Side

