						_							
Form 9-331 (May 1963)	UNITED STATES SUBMIT IN TRIPLICATE® DEPARTMENT OF THE INTERIOR verse side)				Form approved. Budget Bureau No. 48-R1424. 5. LEABE DESIGNATION AND BERIAL NO.								
(Milly 1800)													
		NM-03603-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME											
(Do not t	SUNDRY NO	DTICES AND REPO	ORTS ON or plug back for such prope	WELLS to a different reservoir,	6. IF INDIAN, ALICOTT	EE OR TRIBE NAME							
1. OIL GAS WE'LL WELL X OTHER					7. UNIT AGREEMENT NAME								
2. NAME OF OPERATOR					8. FARM OR LEASE NAME								
R&G Drilling Company c/o Walsh Engr.&Prod. Corp.					Hammond								
3. ADDRESS OF OPERATOR					9. WELL NO.								
P.O. Box 254 Farmington, NM 87401					47-R								
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)					10. FIELD AND POOL, OR WILDCAT								
1550'FSL, 970'FWL					BlancoMesaVerde								
					SURVEY OR ARMA								
					Sec. 35-T27N-R8W N.M.P.M.								
14. PERMIT NO.		15. ELEVATIONS (Show	whether DF, RT	, GR, etc.)	12. COUNTY OR PARIS	SH 18. STATE							
		6306'GR,	6317'DF	'. 6318'KB	San Juan	NewMexic							
16.	Check			ure of Notice, Report, or C	Other Data								
NOTICE OF INTENTION TO:					UENT REPORT OF:								
TEGT WATER	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF				X REPAIRING WELL								
FRACTURE TE		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING	CABING							
SHOOT OR AC		ABANDON*		SHOOTING OR ACIDIZING	ABANDONM	ENT*							
	REPAIR WELL CHANGE PLANS (Other)												
(Other)	(Norge: Report result					s of multiple completion on Well pletion Report and Log form.)							
17. DESCRIBE PRO proposed we nent to this	work. If well is dire	OPERATIONS (Clearly state a sectionally drilled, give subsu	all pertinent d arface location	etails, and give pertinent dates, s and measured and true vertice	including estimated d al depths for all mark	ate of starting any ers and zones perti-							
10-12-77	T.D 3	47'											
Spud Well.													
Ran 8 jts., 8 5/8", 24.0 lb., K-55 casing (322.30') set at 336.05' with 350 sacks Class "B" cement with 2% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Test with 500 psig. Test OK.													
								Tesc Mic	ii Joo parg.	iest Or			
								-					
							-						25
					200,5	ina. The							
					10th com	1 (87) T							
					DIST	Sa. 1							
	•				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	R 1 /							

President, Walsh Engineering

TITLE & Production Co. DATE 10-18-77

TITLE DATE

OCT 19 1977

.

R&G Drilling Company

Ewell N. Walsh, P.E

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

FOR: