

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM-03603-A	
2. NAME OF OPERATOR R&G Drilling Company c/o Walsh Engr.&Prod.Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 254 Farmington, NM 87401		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1550'FSL, 970'FWL		8. FARM OR LEASE NAME Hammond	
14. PERMIT NO.		9. WELL NO. 47-R	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6306'GR, 6317'DF, 6318'KB		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 35-T27N-R8W N.M.P.M.	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)


REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-24-77 T.D. 4900'

Ran 152 jts. 4½", 10.50#, K-55, ST&C casing (4904.20') set at 4914.20' with First Stage - 250 sxs 65/35 Pozmix (12% Gel) with 6 lbs. salt and 6¼ lbs. Gilsonite per sack. Followed by 275 sacks 50/50 Pozmix with 6 lbs. salt and 6¼ lbs. Gilsonite per sack. Second Stage - Stage collar 2500'. 425 sxs 65/35 Pozmix (12% gel) with 6¼ lbs. Gilsonite per sack followed by 50 sxs Class "B" cement. Cement circulated.



For: R&G Drilling Company

18. I hereby certify that the foregoing is true and correct.

SIGNED Rwell N. Walsh, P.E.

TITLE President, Walsh Engineering & Production Corp.

DATE 1-3-78

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
JAN 5 1978

U.S. Geological Survey
Washington, D.C.