UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

			t Burea	No. 42-R	1424
	5. LEASE	7 B B C	50		
	SF 078872A	collin collin collin collin	=	6 2 6	
	6. IF INDIAN,	ALLOTTEE	ORJR	BE NAME	
		6358	ဝိ	المداد رواح: الم	
	7. UNIT AGRE	EMENT N	AME,	5 5 5 2	
nt			1131	15 July 15 Jul	_
	8. FARM OR L		E H	<u> </u>	
	Bolack B	ន <u>ង</u> ខ េត្ត ខេត្ត ខេត្ត ខេត្ត	E Guiter	요 ^를 함.	
	9. WELL NO.	8 1 8 7		Barty Difes	,
	1	3 5 7 8	জু	<u> </u>	
	10. FIELD OR W	/ILDCAT N	AME	24 % F	
	<u> est Kutz</u>	<u> </u>		<u> </u>	
	11. SEC., T., R.	, M., QR B	LK. AN	D SURVE	Y OR
7	AREA		<u>@</u>		
	S.28,T27N,F		<u> </u>		
	12. COUNTY OF				
	<u>San Juan</u>	1,53	New M	lexico	
	14. API NO.	ည့်ဆိုသည်	.⊒.	5 i 5	
Ε,		<u> </u>	5	<u> </u>	
	15. ELEVATION		DF _i K	DB, AND	WD)
	6308 GR	<u> </u>	<u> </u>	5 5	

Suite

(Do not use this form for proposals to drill or to deepen or plug back to a differe reservoir, Use Form 9-331-C for such proposals.) 1. oil gas well well other 2. NAME OF OPERATOR Oklahoma Oil Company 3. ADDRESS OF OPERATOR Dallas, Texas 1120 One Energy Square; 4925 Greenville Ave; 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 AT SURFACE: 1190' FNL & 1550' FEL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: **REQUEST FOR APPROVAL TO:** ede daue risanot v o insarec to qui of TEST WATER SHUT-OFF 3 ₩ 3 FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone change on Form 9-330.) PULL OR ALTER CASING techno brothes change on Form 9-330. MULTIPLE COMPLETE Ξ enoticant 2 operati <u>...</u> 51 5 E C CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 65 gs Gs 67 c 67 c 67 c Spud 5" hole0900 hrs. 8-9-78. Drill to 600' and ream top 45% of hole to 8 3/4". 養育。 Ran 1 jt. 7" surface casing and set at 41'. Cement with 35 sacks Class issu issu cement with 2% CaCl2. Plug down at 1800 hrs. 8-9-78. DIST. Subsurface Safety Valve: Manu. and Type. Ft. 0 18. I hereby certify that the foregoing is true and correct 'n ∾. ğ, Agent SIGNED TITLE lexander (This space for Federal or State office use) 📢 🦠 Š APPROVED BY TITLE DATE CONDITIONS OF APPROVAL IF ANY: Genera 63.10: ALL COL

*See Instructions on Reverse Side